



产品编号：1729531002

系列号：172953

Product Category：Connector Accessories

Product Description：Micro-Fit Terminal
Position Assurance (TPA) Retainer, 10
Circuits, 3.00mm Pitch, UL 94V-2, Glow-
Wire Capable, Natural
状态：Active

文件和资源

图纸

- 图纸 1729531002_sd.pdf
- 包装设计图 1729530001-PK-000.pdf

3D 模型和设计文件

- 3D模型 1729531002_stp.zip

规格

- 产品规格 430450001-PS-K0-000.pdf
- 产品规格 430450001-PS-SP-000.pdf
- 产品规格 PS-43045-001.pdf
- 测试摘要 TS-43045-001-001.pdf
- 测试摘要 TS-43045-002-001.pdf

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Accessories
系列	172953
说明	Micro-Fit Terminal Position Assurance (TPA) Retainer, 10 Circuits, 3.00mm Pitch, UL 94V-2, Glow-Wire Capable, Natural
个评论	See Product Specification for maximum current rating by circuit size and wire AWG; This Molex product is manufactured from material that has the following ratings, tested by independent agencies: a) AGlow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12 and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire; The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s); If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for possible product options.
元件类型	Terminal Position Assurance
产品系列	Micro-Fit Connector System

产品名称	Micro-Fit TPA
UPC	889056430098

物理

回路数（已载入）	10
电路数（最多）	10
颜色-树脂	Natural
锁定插接部位	是
材料 - 树脂	Nylon
净重	0.122/g
行数	1
包装形式	Bag
运行温度范围	-40° to +105° C

可连接使用部件

描述	产品编号
Micro-Fit TPA Receptacle Housings	<u>172952</u>
Micro-Fit TPA Dual Row Plug Housings	<u>203632</u>

