



产品编号：[190010008](#)
Product Description：Avikrimp Quick Disconnect, Male, for 14-16 (2.00-1.30mm²), Box, Tab 4.75 x 0.51mm
系列号：19001
状态：Active
Product Category：Quick Disconnects
工程编号：BB-5268



文件和资源

图纸

[图纸 190010008_sd.pdf](#)

3D 模型和设计文件

[3D模型 190010008_stp.zip](#)

规格

- [产品规格 PS-19902-011-001.pdf](#)
- [产品规格 PS-19902-013-001.pdf](#)
- [产品规格 PS-19902-014-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

[多部分产品合规性声明](#)

- Eu RoHS
- REACH SVHC

- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Quick Disconnects
系列	19001
说明	Avikrimp Quick Disconnect, Male, for 14-16 (2.00-1.30mm ²), Box, Tab 4.75 x 0.51mm
产品系列	Standard Quick-Disconnect Terminals
产品名称	Avikrimp
类型	Quick Disconnect
UPC	800753026629

机构

CSA	LR18689
UL	E79133

电气

电压 - 最大	300V
---------	------

物理

筒型	已关闭
颜色-树脂	蓝色
阻燃性	94V-2
性别	男
符合灼热丝规范	否

绝缘	Fully
绝缘	Nylon (PA)
锁定插接部位	无
材料 - 金属	Brass
材料 - 接合部位电镀	Zinc Chromate
材料 - 终端电镀	Zinc Chromate
净重	1.201/g
方向	Straight
包装形式	Bag
最薄镀层 - 接合部位	5.080µm
最薄镀层 - 端接	5.080µm
有极性的插配件	否
调整片厚度	0.51mm
调整片宽	4.75mm
运行温度范围	-65° to +105° C
导线绝缘直径	4.32mm max.
线径规格 (AWG)	14, 16
线缆尺寸mm ²	1.30-2.00

进程

无铅	不适用
----	-----

可连接使用部件

描述	产品编号
Avikrimp Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Box	/content/molex/molex-dot-com/cn/zh/products/product-page.html/190020028.html
Avikrimp Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Mylar Tape	/content/molex/molex-dot-com/cn/zh/products/product-page.html/190020029.html
Avikrimp Fully Insulated Quick Disconnect, Female, for 14-16 AWG Wire, Metal Strip	/content/molex/molex-dot-com/cn/zh/products/product-page.html/190020030.html

施工工具

全局

描述	产品编号
Hand Crimp Tool	<u>640012600</u>
Crimp Head for the AT-200 Pneumatic Hand Tool	<u>640052600</u>