



产品编号：[194290009](#)

系列号：[19429](#)

Product Category：[Connector Housings](#)

Product Description：[MX150L 4 Circuit Panel Mount Plug for 14-22 AWG Wire, Rear Mount Flange Assembly, without Gasket, Black](#)
状态：[Active](#)

文件和资源

图纸

[图纸 194290009_sd.pdf](#)

[包装设计图 PK-19429-001-001.pdf](#)

3D 模型和设计文件

[3D模型 194290009_stp.zip](#)

规格

[应用规格 AS-19417-001-001.pdf](#)

[产品规格 PS-19417-001-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead monoxide per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

[多部分产品合规性声明](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

产品详情

常规

状态	活动
类别	Connector Housings
系列	19429
说明	MX150L 4 Circuit Panel Mount Plug for 14-22 AWG Wire, Rear Mount Flange Assembly, without Gasket, Black
应用	Power, Wire-to-Wire
个评论	For Inside Panel Mount Application; IP67 rated; Conforms to UL 1977; NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS)
产品系列	MX150L Industrial Sealed Connector System
产品名称	MX150L
UPC	822348564439

机构

UL	E152602
----	---------

物理

电路数（最多）	4
颜色-树脂	黑色
阻燃性	94V-0
性别	Plug
符合灼热丝规范	否
锁定插接部位	是
净重	11.642/g
行数	2
包装形式	Bag

面板安装式	是
间距 - 插配接口	5.84mm
有极性的插配件	是
可堆叠的	否
运行温度范围	-40° to +125° C

可配插/可连接使用的产品

可配插部件

描述	产品编号
MX150L Receptacle Housings	<u>19418</u>

可连接使用部件

描述	产品编号
MX150L Gasket for 4 Circuit Plug Housing with Flange	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/194270024.html</u>
MX150L Male Terminals and Circuit Voiding Keys	<u>19417</u>