



产品编号 : 194290025

**Product Description** : MX150L 4 Circuit Panel Mount Plug for 14-22 AWG Wire, Through Hole Flange Assembly, without Gasket, Black

系列号 : 19429

**状态** : Active

**Product Category** : Connector Housings

---

## 文件和资源

### 图纸

图纸 194290025\_sd.pdf

包装设计图 PK-19429-001-001.pdf

### 3D 模型和设计文件

3D模型 194290025\_stp.zip

### 规格


应用规格 AS-19417-001-001.pdf

产品规格 PS-19417-001-001.pdf

---

## 产物环境合规

### 合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
  
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## 产品详情

## 常规

状态	活动
类别	Connector Housings
系列	19429
说明	MX150L 4 Circuit Panel Mount Plug for 14-22 AWG Wire, Through Hole Flange Assembly, without Gasket, Black
应用	Power, Wire-to-Wire
个评论	For Outside or Inside Panel Mount Application; IP67 rated; Conforms to UL 1977; NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS)
产品系列	MX150L Industrial Sealed Connector System
产品名称	MX150L
UPC	822348564446

## 物理

电路数（最多）	4
颜色-树脂	黑色
性别	Plug
符合灼热丝规范	否
锁定插接部位	是
净重	9.524/g
行数	2
包装形式	Bag
面板安装式	是
间距 - 插配接口	5.84mm
有极性的插配件	是
可堆叠的	否

运行温度范围	-40° to +125° C
--------	-----------------

---

## 可配插/可连接使用的产品

### 可配插部件

描述	产品编号
MX150L Receptacle Housings	<u>19418</u>

### 可连接使用部件

描述	产品编号
MX150L Gasket for 2 Circuit Plug Housing with Flange	<u><a href="/content/molex/molex-dot-com/cn/zh/products/product-page.html/194270025.html">/content/molex/molex-dot-com/cn/zh/products/product-page.html/194270025.html</a></u>
MX150L Male Terminals and Circuit Voiding Keys	<u>19417</u>