



产品编号 : 194290046

Product Description : MX150L 10 Circuit Panel Mount Plug for 14-22 AWG Wire, Through Hole Flange Assembly, with Gasket, Black

系列号 : 19429

状态 : Active

Product Category : Connector Housings

文件和资源

图纸

图纸 194290046_sd.pdf

包装设计图 PK-19429-001-001.pdf

3D 模型和设计文件

3D模型 194290046_stp.zip


规格

应用规格 AS-19417-001-001.pdf

产品规格 PS-19417-001-001.pdf

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

产品详情

常规

状态	活动
类别	Connector Housings
系列	19429
说明	MX150L 10 Circuit Panel Mount Plug for 14-22 AWG Wire, Through Hole Flange Assembly, with Gasket, Black
应用	Power, Wire-to-Wire
个评论	For Outside or Inside Panel Mount Application; IP67 rated; Conforms to UL 1977; NOT suitable for automotive applications with requirements such as USCAR-2, USCAR-25, GMW3191, AK Testing, J2030, Volvo Technology Requirements, and Toyota Connector Spec (TCS)
产品系列	MX150L Industrial Sealed Connector System
产品名称	MX150L
UPC	822348615148

机构

CSA	LR18689
UL	E152602

物理

电路数 (最多)	10
颜色-树脂	黑色
阻燃性	94V-0
性别	Plug
符合灼热丝规范	否
锁定插接部位	是
净重	17.917/g
行数	2

包装形式	Bag
面板安装式	是
间距 - 插配接口	5.84mm
有极性的插配件	是
可堆叠的	否
运行温度范围	-40° to +125° C

可配插/可连接使用的产品

可配插部件

描述	产品编号
MX150L Receptacle Housings	<u>19418</u>

可连接使用部件

描述	产品编号
MX150L Male Terminals and Circuit Voiding Keys	<u>19417</u>