



产品编号 : 29110043

系列号 : 5240

Product Category : Connector Housings

Product Description : 2.50mm Pitch Mini-Latch Wire-to-Wire Plug Housing, Friction Lock, without Mounting Ears, 4 Circuits, Natural


状态 : New Business Not Supported

工程编号 : 5240-041

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	New Business Not Supported
类别	Connector Housings

系列	5240
说明	2.50mm Pitch Mini-Latch Wire-to-Wire Plug Housing, Friction Lock, without Mounting Ears, 4 Circuits, Natural
应用	Signal, Wire-to-Wire
产品系列	Mini-Latch Wire-to-Board / Wire-to-Wire Connector System
产品名称	Mini-Latch
UPC	800753585126

机构

CSA	LR19980
UL	E29179

物理

电路数（最多）	4
颜色-树脂	Natural (White)
阻燃性	94V-0
性别	Plug
符合灼热丝规范	否
锁定插接部位	是
净重	679.400/mg
行数	1
包装形式	Bag
面板安装式	是
间距 - 插配接口	2.50mm
可堆叠的	否
运行温度范围	-40° to +105° C