



产品编号：[330013006](#)

Product Description：MX150 Female Terminal for Mat-Sealed Connectors, Gold Plating, Grip Code M3, Preferred Terminal for use in Sealed Application with 0.35-0.50mm², Left Reel Payoff

系列号：33001

状态：Active

Product Category：Crimp Terminals



文件和资源

图纸

[图纸 330013006_sd.pdf](#)

规格

[测试摘要 TS-33001-002-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Duty-To-Declare
China RoHS	Not Relevant
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

[多部分产品合规性声明](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[多部分行业合规性文件](#)

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

产品详情

常规

状态	活动
类别	Crimp Terminals
系列	33001
说明	MX150 Female Terminal for Mat-Sealed Connectors, Gold Plating, Grip Code M3, Preferred Terminal for use in Sealed Application with 0.35-0.50mm², Left Reel Payoff
应用	Power, Wire-to-Board, Wire-to-Wire
个评论	Left Reel Payoff, Small Polarization Rib
产品系列	MX150 Sealed and Unsealed Connector System
产品名称	MX150
UPC	884982250840

电气

每触点最大电流	Contact Molex
电压 - 最大	14V DC

物理

性别	女
夹具代码	M3
材料 - 金属	High Performance Alloy (HPA)
材料 - 接合部位电镀	金牌
材料 - 终端电镀	Tin
净重	0.435/g
包装形式	Reel
最薄镀层 - 接合部位	0.762µm
最薄镀层 - 端接	2.540µm
终端界面类型	Crimp or Compression

导线绝缘直径	1. 70mm max.
线径规格 (AWG)	不适用
线缆尺寸mm ²	0. 35–0. 50

可连接使用部件

描述	产品编号
MX150 Mat-Sealed Dual Row Female Connector Assemblies	<u>33472</u>
MX150 Mat-Sealed Single Row Female Connector Assemblies	<u>33471</u>

施工工具

全局

描述	产品编号
Extraction Toolkit for MX150 Connectors	<u>2002220700</u>
FA2 Mechanical Feed Applicator for MX150 Female Terminals, 0. 35mm ² and 0. 50mm ² ISO Wire	<u>638082500</u>
Extraction Tool for MX150L, MX150, PT Bulb Socket, iGrid, SPOX, and Wire-to-Motor Terminals	<u>638131500</u>
Hand Crimp Tool for ISO (M3) Receptacle Terminals	<u>638233700</u>
FineAdjust Applicator for SRC Connector using MX150 Receptacle Terminals, 0. 50mm ² wires	<u>639041200</u>