



产品编号：334721607

系列号：33472

Product Category：Connector Housings

Product Description：MX150 Mat-Sealed Female Connector Assembly, Dual Row, 16 Circuits, Keying Option B, with Connector Position Assurance, Light Gray

状态：Active

文件和资源

图纸

图纸 334721607_sd.pdf

3D 模型和设计文件

3D模型 334721607_stp.zip

规格

应用规格 AS-33472-100-001.pdf

应用规格 AS-33472-100-CH-001.pdf

应用规格 AS-33611-001-001.pdf

产品规格 PS-33472-000-001.pdf

测试摘要 TS-33472-0001-001.pdf

产物环境合规

合规

GADSL/IMDS	Duty-To-Declare
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Housings
系列	33472
说明	MX150 Mat-Sealed Female Connector Assembly, Dual Row, 16 Circuits, Keying Option B, with Connector Position Assurance, Light Gray
应用	Power, Wire-to-Board, Wire-to-Wire
产品系列	MX150 Sealed and Unsealed Connector System
产品名称	MX150
UPC	756054662083

机构

UL	E29179
----	--------

物理

电路数（最多）	16
颜色-树脂	Gray (Light)
性别	Receptacle
符合灼热丝规范	否
插接极性	是
锁定插接部位	是
材料 - 树脂	SPS/Nylon
净重	18.400/g
行数	2
包装形式	Partitioned Carton
面板安装式	否
间距 - 插配接口	3.50mm

有极性的插配件	是
可堆叠的	否
运行温度范围	-40° to +125° C

进程

无铅	不适用
----	-----

可配插/可连接使用的产品

可配插部件

描述	产品编号
MX150 2x4 Dual Row Right-Angle Header, 8 Circuits, Keying Option D, Black, Solder Tail	<u>348300804</u>
MX150 Male Connector Assembly, Bulkhead Twist-Lock, Mat-Sealed Compatible, Dual Row, 16 Circuits, Keying Option B, Light Gray	<u>348408420</u>
MX150 Mat-Sealed Dual Row Male Connector Assemblies	<u>33482</u>

可连接使用部件

描述	产品编号
MX150 Sealed Cavity Plug	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/343450001.html</u>
MX150 Female Terminals	<u>33001</u>
MX150 Female Terminals	<u>33012</u>