



产品编号 : 334724001

系列号 : 33472

Product Category : Connector Housings

Product Description : MX150 Mat-Sealed Female Connector Assembly, Dual Row, 4 Circuits, Keying Option A, without Connector Position Assurance, with Open Standard Grommet Cap, Black

状态 : Active

文件和资源

图纸

图纸 334724001_sd.pdf

3D 模型和设计文件

3D模型 334724001_stp.zip

规格

应用规格 AS-33472-100-001.pdf

应用规格 AS-33472-100-CH-001.pdf

应用规格 AS-33611-001-001.pdf

产物环境合规

合规

GADSL/IMDS	Compliant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Housings
系列	33472
说明	MX150 Mat-Sealed Female Connector Assembly, Dual Row, 4 Circuits, Keying Option A, without Connector Position Assurance, with Open Standard Grommet Cap, Black
应用	Power, Wire-to-Board, Wire-to-Wire
产品系列	MX150 Sealed and Unsealed Connector System
产品名称	MX150
UPC	889056506366

机构

UL	E29179
----	--------

物理

电路数（最多）	4
颜色-树脂	黑色
性别	Receptacle
符合灼热丝规范	否
插接极性	是
锁定插接部位	是
材料 - 树脂	SPS/Nylon
净重	8.180/g
行数	2
包装形式	Partitioned Carton

面板安装式	否
间距 - 插配接口	3.50mm
有极性的插配件	是
可堆叠的	否
运行温度范围	-40° to +125° C

可配插/可连接使用的产品

可配插部件

描述	产品编号
MX150 Mat-Sealed Dual Row Male Connector Assemblies	<u>33482</u>

可连接使用部件

描述	产品编号
MX150 Sealed Cavity Plug	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/343450001.html</u>
MX150 Female Terminals	<u>33001</u>
MX150 Female Terminals	<u>33012</u>