



产品编号：334822004

系列号：33482

Product Category：Connector Housings

Product Description：MX150 Sealed Male Connector, Dual Row, 20 Circuits, Polarization D, without Connector Position Assurance, Green; For USCAR Compliance, Use Alternate Part Number: 334822055

状态：Obsolete

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Reviewed
China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	Obsolete
类别	Connector Housings
系列	33482

说明	MX150 Sealed Male Connector, Dual Row, 20 Circuits, Polarization D, without Connector Position Assurance, Green; For USCAR Compliance, Use Alternate Part Number: 334822055
应用	Power, Wire-to-Wire
个评论	No Connector Position Assurance (CPA)
产品系列	MX150 Sealed and Unsealed Connector System
产品名称	MX150
UPC	883906522476

机构

UL	E29179
----	--------

物理

电路数（最多）	20
颜色-树脂	Green, Natural
性别	Plug
符合灼热丝规范	否
插接极性	是
锁定插接部位	是
材料 - 树脂	SPS/Nylon
净重	21.645/g
行数	2
包装形式	Bag
面板安装式	否
间距 - 插配接口	3.50mm
有极性的插配件	是
可堆叠的	否
运行温度范围	-40° to +125° C