



产品编号 : 351550200

Product Description : 2.50mm Pitch Wire-to-Board Housing, Positive Lock, Natural, 2 Circuits

系列号 : 35155


状态 : New Business Not Supported

Product Category : Connector Housings

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	New Business Not Supported
类别	Connector Housings
系列	35155

说明	2.50mm Pitch Wire-to-Board Housing, Positive Lock, Natural, 2 Circuits
应用	Signal, Wire-to-Wire
产品名称	不适用
UPC	800753683907

机构

CSA	LR19980
UL	E29179

物理

断开	否
电路数 (最多)	2
颜色-树脂	Natural
阻燃性	94V-0
性别	Receptacle
符合灼热丝规范	否
插接极性	无
锁定插接部位	是
材料 - 树脂	Polyester
净重	0.300/g
行数	1
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.50mm
间距 - 终端界面	2.50mm
运行温度范围	-40° to +105° C