



产品编号：353630660

系列号：35363

Product Category：PCB Headers and Receptacles

Product Description：2.00mm Pitch Sherlock Wire-to-Board Header, Right-Angle, with Positive Lock, 6 Circuits

状态：New Business Not Supported


---

## 文件和资源

---

## 产物环境合规

### 合规

GADSL/IMDS	Compliant with Exemption 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
  
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### 欧盟 RoHS 合格证书

---

## 产品详情

### 常规

状态	New Business Not Supported
类别	PCB Headers and Receptacles
系列	35363

说明	2.00mm Pitch Sherlock Wire-to-Board Header, Right-Angle, with Positive Lock, 6 Circuits
应用	Signal, Wire-to-Board
元件类型	PCB Header
产品系列	Sherlock Wire-to-Board Connector System
产品名称	Sherlock
UPC	822348260461

## 机构

CSA	LR19980
UL	E29179

## 电气

每触点最大电流	2.0A
电压 - 最大	125V

## 物理

断开	否
回路数 (已载入)	6
电路数 (最多)	6
颜色-树脂	Natural
耐用性(插拔次数) - 最多次数	30
先接后断	否
阻燃性	94V-0
符合灼热丝规范	否
可配插产品指南	否
插接极性	无
锁定插接部位	是
材料 - 接合部位电镀	Tin
材料 - 终端电镀	Tin
材料 - 树脂	Nylon
净重	0.440/g
行数	1
方向	Right Angle

包装形式	Bag
PC 焊脚长度	3.20mm
PCB 定位器	否
PCB 保持力	是
推荐的 PCB 厚度	1.60mm
间距 - 插配接口	2.00mm
有极性的插配件	是
PCB 极性	否
有护墙的	Partial
可堆叠的	否
运行温度范围	-40° to +105° C
终端界面类型	Through Hole

---

This document was generated on Jun 30, 2024