




产品编号 : 5015913411

Product Description : SlimStack Board-to-Board Receptacle, 0.40mm Pitch, Surface Mount, Dual Row, Vertical Stacking, 0.90mm Stacking Height, with Solder Tabs, 34 Circuits

系列号 : 501591

状态 : Obsolete

Product Category : Board-to-Board Connectors



文件和资源

产物环境合规

合规

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	Obsolete
类别	Board-to-Board Connectors
系列	501591
说明	SlimStack Board-to-Board Receptacle, 0.40mm Pitch, Surface Mount, Dual Row, Vertical Stacking, 0.90mm Stacking Height, with Solder Tabs, 34 Circuits
应用	Board-to-Board, Signal
元件类型	PCB Receptacle
产品系列	SlimStack Board-to-Board/Board-to-FPC Connectors
产品名称	SlimStack
UPC	800756662367

机构

UL	E29179
----	--------

电气

每触点最大电流	0.3A
电压 - 最大	50V AC (RMS)/DC

物理

回路数 (已载入)	34
电路数 (最多)	34
颜色-树脂	黑色
耐用性(插拔次数) - 最多次数	20
阻燃性	94V-0
符合灼热丝规范	否
锁定插接部位	是
插配长度	0.90mm
插配宽度	3.40mm
材料 - 金属	Phosphor Bronze
材料 - 接合部位电镀	金牌
净重	37.733/mg

行数	2
方向	垂直
包装形式	Embossed Tape on Reel
PCB 定位器	否
PCB 保持力	是
间距 - 插配接口	0.40mm
间距 - 终端界面	0.40mm
有极性的插配件	否
PCB 极性	否
运行温度范围	-25° to +85° C
终端界面类型	Surface Mount

This document was generated on Jan 30, 2024