



产品编号 : 5031103000

系列号 : 503110

Product Category : Connector Housings

Product Description : 1.25mm Pitch Duo-Clasp Wire-to-Board Housing, Dual Row, Positive Lock, 30 Circuits, White

状态 : New Business Not Supported


---

## 文件和资源

---

## 产物环境合规

### 合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
  
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### 欧盟 RoHS 合格证书

---

## 产品详情

### 常规

状态	New Business Not Supported
类别	Connector Housings
系列	503110

说明	1.25mm Pitch Duo-Clasp Wire-to-Board Housing, Dual Row, Positive Lock, 30 Circuits, White
应用	Signal, Wire-to-Board
产品名称	Duo-Clasp
UPC	800756934129

## 机构

UL	E29179
----	--------

## 物理

断开	否
电路数 (最多)	30
颜色-树脂	白色
性别	Plug
符合灼热丝规范	否
插接极性	是
锁定插接部位	是
净重	434.000/mg
行数	2
包装形式	Bag
面板安装式	否
间距 - 插配接口	1.25mm
间距 - 终端界面	1.25mm
有极性的插配件	是
端口	1
可堆叠的	否
运行温度范围	-25° to +85° C