



产品编号 : 511020200

Product Description : 2.50mm Pitch Mini-Lock Wire-to-Board Housing, Friction Lock, 2 Circuits, Natural

系列号 : 51102


状态 : New Business Not Supported

Product Category : Connector Housings

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	New Business Not Supported
类别	Connector Housings
系列	51102

说明	2.50mm Pitch Mini-Lock Wire-to-Board Housing, Friction Lock, 2 Circuits, Natural
应用	Signal, Wire-to-Board, Wire-to-Wire
产品系列	Mini-Lock Wire-to-Board Connector System
产品名称	Mini-Lock
UPC	800753683471

物理

电路数 (最多)	2
颜色-树脂	Natural
性别	Receptacle
符合灼热丝规范	否
插接极性	无
锁定插接部位	是
材料 - 树脂	Polyester
净重	180.900/mg
行数	1
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.50mm
可堆叠的	否
运行温度范围	-40° to +105° C