



产品编号 : [511030900](#)

Product Description : 2.50mm Pitch, Mini-Lock Receptacle Crimp Housing, Single Row, Positive Lock, 9 Circuits, Natural

系列号 : 51103

状态 : New Business Not Supported

Product Category : Connector Housings



---

## 文件和资源

---

### 产物环境合规

#### 合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

#### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### 多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### 欧盟 RoHS 合格证书

---

## 产品详情

#### 常规

状态	New Business Not Supported
类别	Connector Housings
系列	51103
说明	2.50mm Pitch, Mini-Lock Receptacle Crimp Housing, Single Row, Positive Lock, 9 Circuits, Natural
应用	Signal, Wire-to-Wire
产品系列	Mini-Lock Wire-to-Board Connector System
产品名称	Mini-Lock
UPC	800754307239

### 机构

CSA	LR19980
UL	E29179

### 物理

电路数（最多）	9
颜色-树脂	Natural
阻燃性	94V-0
性别	Receptacle
符合灼热丝规范	否
插接极性	无
材料 - 树脂	Polyester
净重	664.100/mg
行数	1
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.50mm
可堆叠的	否
运行温度范围	-40° to +105° C