




产品编号 : 511161601

Product Description : 4.00mm Pitch, OBD-II Wire-to-Wire Receptacle Housing, Flange Mount, 16 Circuits

系列号 : 51116

状态 : New Business Not Supported

Product Category : Connector Housings



---

## 文件和资源

---

### 产物环境合规

#### 合规

GADSL/IMDS	Duty-To-Declare
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

#### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### 多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### 欧盟 RoHS 合格证书

---

## 产品详情

#### 常规

状态	New Business Not Supported
类别	Connector Housings
系列	51116
说明	4.00mm Pitch, OBD-II Wire-to-Wire Receptacle Housing, Flange Mount, 16 Circuits
应用	Power, Wire-to-Wire
产品名称	OBD-II
UPC	800754236980

## 物理

电路数 (最多)	16
颜色-树脂	黑色
性别	Receptacle
符合灼热丝规范	否
插接极性	无
锁定插接部位	是
材料 - 树脂	Polyester
净重	10474.200/mg
行数	2
包装形式	Bag
面板安装式	否
间距 - 插配接口	4.00mm
可堆叠的	否
运行温度范围	-40° to +85° C

## 进程

无铅	不适用
----	-----