



产品编号 : 527451433

系列号 : 52745

Product Category : FFC / FPC Connectors


Product Description : Easy-On FFC/FPC Connector, 0.50mm Pitch, Slider Series, Right-Angle, Top Contact, 2.00mm Height, 14 Circuits, Tin-Silver-Bismuth Plating

状态 : Obsolete

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	Obsolete
类别	FFC / FPC Connectors

系列	52745
说明	Easy-On FFC/FPC Connector, 0.50mm Pitch, Slider Series, Right-Angle, Top Contact, 2.00mm Height, 14 Circuits, Tin-Silver-Bismuth Plating
产品系列	Slider
产品系列	Easy-On FFC FPC Connectors
产品名称	Easy-On
UPC	887191284309

机构

UL	E29179
----	--------

电气

每触点最大电流	0.5A
电压 - 最大	50V

物理

驱动器类型	Slider
回路数 (已载入)	14
颜色-树脂	Black, White
接触部位	顶部
耐用性(插拔次数) - 最多次数	20
阻燃性	94V-0
插配长度	2.00mm
材料 - 金属	Phosphor Bronze
材料 - 接合部位电镀	Tin-Silver-Bismuth
材料 - 终端电镀	Tin-Silver-Bismuth
材料 - 树脂	Nylon
净重	190.820/mg
方向	Right Angle
包装形式	Embossed Tape on Reel
PC 焊脚长度	2.00mm
PCB 定位器	否
PCB安装	Surface Mount

PCB 保持力	是
间距 - 插配接口	0.50mm
间距 - 终端界面	0.50mm
PCB 极性	是
可堆叠的	否
运行温度范围	-40° to +85° C
导线/电缆型号	FFC/FPC

This document was generated on Jun 04, 2024