



产品编号 : 541670308

Product Description : 0.50mm Pitch SlimStack Receptacle, Surface Mount, Dual Row, Vertical, 3.00 and 4.00mm Stacking Heights, Lower Circuit Size Version, Black, 30 Circuits

系列号 : 54167


状态 : Obsolete

Product Category : Board-to-Board Connectors

文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	Obsolete
----	----------

类别	Board-to-Board Connectors
系列	54167
说明	0.50mm Pitch SlimStack Receptacle, Surface Mount, Dual Row, Vertical, 3.00 and 4.00mm Stacking Heights, Lower Circuit Size Version, Black, 30 Circuits
应用	Board-to-Board, Signal
元件类型	PCB Receptacle
产品系列	SlimStack Board-to-Board/Board-to-FPC Connectors
产品名称	SlimStack
UPC	800754250351

电气

每触点最大电流	0.5A
电压 - 最大	50V

物理

回路数 (已载入)	30
电路数 (最多)	30
符合灼热丝规范	否
插配长度	3.00mm, 4.00mm
插配宽度	5.40mm
材料 - 接合部位电镀	金牌
材料 - 终端电镀	金牌
净重	125.201/mg
行数	2
方向	垂直
包装形式	Embossed Tape on Reel
PCB 定位器	否
PCB 保持力	无
推荐的 PCB 厚度	1.60mm
间距 - 插配接口	0.50mm
最薄镀层 - 接合部位	0.102µm
最薄镀层 - 端接	0.254µm
PCB 极性	否

运行温度范围	-40° to +105° C
终端界面类型	Surface Mount

This document was generated on Jun 04, 2024