

勝特力電材超市-龍山店 886-3-5773766
 勝特力電材超市-光復店 886-3-5729570
 勝特力電子(上海) 86-21-34970699
 勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>

PLUG MOLD COVER B	51236-1205	1	51236-2005	1	51236-3005	1
PLUG MOLD COVER A	51235-1215	1	51235-2015	1	51235-3015	1
CROSS RECESSED HEAD SCREW	58203-0020	2	58203-0020	2	58203-0021	2
CABLE CLAMP	56382-1200	1	56382-2000	1	56382-3000	1
PLUG SHELL COVER	56381-1228	1	56381-2028	1	56381-3028	1
PLUG SHELL BODY	56380-1228	1	56380-2028	1	56380-3028	1
PLUG PIN HS'G	51234-1201	1	51234-2001	1	51234-3001	1
部品名称 PART NAME	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.
極数 CIRCUIT	12		20		30	
セット型番 SET NO.	55836-1270		55836-2070		55836-3070	
タイプ TYPE	STANDARD TYPE					

55836-3074	55836-xx74
55836-2074	
55836-1274	
55836-3073	55836-xx73
55836-2073	
55836-1273	
55836-3072	55836-xx72
55836-2072	
55836-1272	
55836-3071	55836-xx71
55836-2071	
55836-1271	
55836-3070	55836-xx70
55836-2070	
55836-1270	
MATERIAL NO.	MODEL NO.

注記
NOTES

- 本製品は 55836-xx0* の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 55836-xx0*.

RELEASED EC NO: J2006-1791 DRWN: MABE1 2005/11/30 CHKDK: TOYODA 2005/12/01 APPR: NUKITA 2005/12/06	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
	10 UNDER	±0.2	DRAWN BY M. NABE I		DATE '05/11/29	TITLE COMPACT ROBOT CONN. PLUG PIN SET -LEAD FREE-			
	10 OVER 30 UNDER	±0.25	CHECKED BY K. TOYODA		DATE '05/11/29				
	30 OVER	±0.3	APPROVED BY N. UKITA		DATE '05/11/29	MOLEX INCORPORATED			
	ANGULAR	±3 °	MATERIAL NO.		DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-55836-006		1 OF 5			

SIZE
A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

F

E

D

C

B

A

PLUG MOLD COVER B	51236-1205	1	51236-2005	1	51236-3005	1
PLUG MOLD COVER A	51235-1215	1	51235-2015	1	51235-3015	1
CROSS RECESSED HEAD SCREW	58203-0020	2	58203-0020	2	58203-0021	2
CABLE CLAMP	56382-1200	1	56382-2000	1	56382-3000	1
PLUG SHELL COVER	56381-1228	1	56381-2028	1	56381-3028	1
PLUG SHELL BODY	56380-1228	1	56380-2028	1	56380-3028	1
PLUG PIN HS'G	51234-1202	1	51234-2002	1	51234-3002	1
部品名称 PART NAME	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.
極数 CIRCUIT	12		20		30	
セット型番 SET NO.	55836-1271		55836-2071		55836-3071	
タイプ TYPE	A TYPE					

F

E

D

C

B

A

RELEASED EC NO: J2006-1791 DRWN: NABE1 2005/11/30 CHKDK: TOYODA 2005/12/01 APPR: NUKITA 2005/12/06	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
	10 UNDER	±0.2	DRAWN BY M. NABE1		DATE '05/11/29	TITLE COMPACT ROBOT CONN. PLUG PIN SET -LEAD FREE-			
	10 OVER 30 UNDER	±0.25	CHECKED BY K. TOYODA		DATE '05/11/29				
	30 OVER	±0.3	APPROVED BY N. UKITA		DATE '05/11/29	MOLEX INCORPORATED			
	ANGULAR	±3 °	MATERIAL NO.		DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		SEE CHART		SD-55836-006		2 OF 5	

F

E

D

C

B

A

PLUG MOLD COVER B	51236-1205	1	51236-2005	1	51236-3005	1
PLUG MOLD COVER A	51235-1215	1	51235-2015	1	51235-3015	1
CROSS RECESSED HEAD SCREW	58203-0020	2	58203-0020	2	58203-0021	2
CABLE CLAMP	56382-1200	1	56382-2000	1	56382-3000	1
PLUG SHELL COVER	56381-1228	1	56381-2028	1	56381-3028	1
PLUG SHELL BODY	56380-1228	1	56380-2028	1	56380-3028	1
PLUG PIN HS'G	51234-1203	1	51234-2003	1	51234-3003	1
部品名称 PART NAME	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.
極数 CIRCUIT	12		20		30	
セット型番 SET NO.	55836-1272		55836-2072		55836-3072	
タイプ TYPE	B TYPE					

F

E

D

C

B

A

RELEASED EC NO: J2006-1791 DRW: M.NABE 2005/11/30 CHK: K.TOYODA 2005/12/01 APP: N.UKITA 2005/12/06	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
	10 UNDER	±0.2	DRAWN BY M.NABE I		DATE '05/11/29		TITLE COMPACT ROBOT CONN. PLUG PIN SET -LEAD FREE-		
	10 OVER 30 UNDER	±0.25	CHECKED BY K.TOYODA		DATE '05/11/29				
	30 OVER	±0.3	APPROVED BY N.UKITA		DATE '05/11/29		MOLEX INCORPORATED		
	ANGULAR	±3 °	MATERIAL NO.		DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE CHART		SD-55836-006		3 OF 5		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

F

F

E

E

D

D

C

C

B

B

A

A

PLUG MOLD COVER B	51236-1205	1	51236-2005	1	51236-3005	1
PLUG MOLD COVER A	51235-1215	1	51235-2015	1	51235-3015	1
CROSS RECESSED HEAD SCREW	58203-0020	2	58203-0020	2	58203-0021	2
CABLE CLAMP	56382-1200	1	56382-2000	1	56382-3000	1
PLUG SHELL COVER	56381-1228	1	56381-2028	1	56381-3028	1
PLUG SHELL BODY	56380-1228	1	56380-2028	1	56380-3028	1
PLUG PIN HS'G	51234-1204	1	51234-2004	1	51234-3004	1
部品名称 PART NAME	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.
極数 CIRCUIT	12		20		30	
セット型番 SET NO.	55836-1273		55836-2073		55836-3073	
タイプ TYPE	C TYPE					

RELEASED EC NO: J2006-1791 DRW: M.NABE 2005/11/30 CHK: K.TOYODA 2005/12/01 APP: N.UKITA 2005/12/06	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
	10 UNDER	±0.2	DRAWN BY M.NABE I		DATE '05/11/29		TITLE COMPACT ROBOT CONN. PLUG PIN SET -LEAD FREE-		
	10 OVER 30 UNDER	±0.25	CHECKED BY K.TOYODA		DATE '05/11/29				
	30 OVER	±0.3	APPROVED BY N.UKITA		DATE '05/11/29		MOLEX INCORPORATED		
	ANGULAR	±3 °	MATERIAL NO.		DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE CHART		SD-55836-006		4 OF 5		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									

F

E

D

C

B

A

PLUG MOLD COVER B	51236-1205	1	51236-2005	1	51236-3005	1
PLUG MOLD COVER A	51235-1215	1	51235-2015	1	51235-3015	1
CROSS RECESSED HEAD SCREW	58203-0020	2	58203-0020	2	58203-0021	2
CABLE CLAMP	56382-1200	1	56382-2000	1	56382-3000	1
PLUG SHELL COVER	56381-1228	1	56381-2028	1	56381-3028	1
PLUG SHELL BODY	56380-1228	1	56380-2028	1	56380-3028	1
PLUG PIN HS'G	51234-1205	1	51234-2005	1	51234-3005	1
部品名称 PART NAME	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.	部品型番 PART NO.	数量 QUAN.
極数 CIRCUIT	12		20		30	
セット型番 SET NO.	55836-1274		55836-2074		55836-3074	
タイプ TYPE	D TYPE					

RELEASED EC NO: J2006-1791 DRW: M.NABE 2005/11/30 CHK: K.TOYODA 2005/12/01 APP: N.UKITA 2005/12/06	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
	10 UNDER	±0.2	DRAWN BY M.NABE I		DATE '05/11/29	TITLE COMPACT ROBOT CONN. PLUG PIN SET -LEAD FREE-			
	10 OVER 30 UNDER	±0.25	CHECKED BY K.TOYODA		DATE '05/11/29				
	30 OVER	±0.3	APPROVED BY N.UKITA		DATE '05/11/29	MOLEX INCORPORATED DOCUMENT NO. SD-55836-006 SHEET NO. 5 OF 5			
	ANGULAR	±3 °	MATERIAL NO.		SEE CHART				
0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				



产品编号 : [558362070](#)

Product Description : CRC Shielded Rectangular I/O Plug Assembly Set, Male Terminal, Signal, 20 Circuits, Polarization Type Standard, Lead-Free

系列号 : 55836

状态 : Active

Product Category : I/O Connectors



文件和资源

图纸


[图纸 558362070_sd.pdf](#)

规格

[产品规格 PS-51238-018-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

产品详情

常规

状态	活动
类别	I/O Connectors
系列	55836
说明	CRC Shielded Rectangular I/O Plug Assembly Set, Male Terminal, Signal, 20 Circuits, Polarization Type Standard, Lead-Free
应用	Wire-to-Wire
元件类型	Kit
产品系列	CRC (Compact Robotic Connectors)
产品名称	CRC
类型	不适用
UPC	822350369503

电气

每触点最大电流	3.5A
屏蔽形式	Full Shield
屏蔽	是
电压 - 最大	250V AC (RMS)/DC

物理

回路数 (已载入)	20
电路数 (最多)	20
颜色-树脂	Black, Gray
耐用性(插拔次数) - 最多次数	100
性别	Plug
插接极性	是
锁定插接部位	是
材料 - 金属	Phosphor Bronze, Stainless Steel
材料 - 接合部位电镀	金牌
材料 - 树脂	Polyester

净重	38101.728/mg
行数	5
方向	垂直
包装形式	Tray
面板安装式	否
PCB 定位器	否
间距 - 插配接口	3.00mm
间距 - 终端界面	3.00mm
有极性的插配件	是
PCB 极性	否
运行温度范围	-40° to +105° C
终端界面类型	Crimp or Compression
防水/防尘	否

可配插/可连接使用的产品

可配插部件

描述	产品编号
CRC Shielded Rectangular I/O Receptacle Assembly Sets	<u>54333</u>
CRC Shielded Rectangular I/O Receptacle Assembly Sets	<u>54334</u>