



产品编号 : 901420006

Product Description : 2.54mm Pitch C-Grid
III Crimp Housing Dual Row, 6 Circuits,
Black

系列号 : 90142

状态 : Active

Product Category : Connector Housings

文件和资源

图纸

图纸 901420006_sd.pdf

3D 模型和设计文件


3D模型 901420006_stp.zip

规格

产品规格 PS-99020-0001-001.pdf

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Housings
系列	90142
说明	2.54mm Pitch C-Grid III Crimp Housing Dual Row, 6 Circuits, Black
应用	Signal, Wire-to-Board
产品系列	C-Grid III Interconnects
产品名称	C-Grid III
UPC	800753659049

机构

CSA	LR19980
UL	E29179

物理

断开	否
电路数 (最多)	6
颜色-树脂	黑色
性别	Receptacle
符合灼热丝规范	否
插接极性	无
锁定插接部位	是
材料 - 树脂	PPO
净重	0.420/g
行数	2
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.54mm
间距 - 终端界面	2.54mm
有极性的插配件	是
端口	0
可堆叠的	否

运行温度范围	-55° to +105° C
--------	-----------------

进程

无铅	不适用
----	-----

可配插/可连接使用的产品

可配插部件

描述	产品编号
C-Grid III Right-Angle Dual Row Headers	<u>90122</u>
C-Grid III Dual Row Headers	<u>90130</u>
C-Grid III Vertical Dual Row Headers	<u>90131</u>

可连接使用部件

描述	产品编号
Pre-Crimped Lead C-Grid III Female-to-C-Grid III Female, Tin (Sn) Plating, 150.00mm Length, 22 AWG, Black	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582022.html</u>
Pre-Crimped Lead C-Grid III Female-to-C-Grid III Female, Tin (Sn) Plating, 300.00mm Length, 22 AWG, Black	<u>/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582023.html</u>
C-Grid III Female Crimp Terminals	<u>90119</u>