



产品编号 : [901560143](#)

Product Description : 2.54mm Pitch C-Grid III Crimp Housing Single Row, 3 Circuits, Black

系列号 : 90156

状态 : Active

Product Category : Connector Housings



文件和资源

图纸

[图纸 901560143_sd.pdf](#)

[包装设计图 PK-90156-0001-001.pdf](#)

3D 模型和设计文件

[3D模型 901560143_stp.zip](#)

规格

[应用规格 901190001-AS-000.pdf](#)

[产品规格 PS-99020-0001-001.pdf](#)

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	活动
类别	Connector Housings
系列	90156
说明	2.54mm Pitch C-Grid III Crimp Housing Single Row, 3 Circuits, Black
应用	Signal, Wire-to-Board
产品系列	C-Grid III Interconnects
产品名称	C-Grid III
UPC	800753668140

机构

CSA	LR19980
UL	E29179

物理

断开	否
电路数 (最多)	3
颜色-树脂	黑色
性别	Receptacle
符合灼热丝规范	否
锁定插接部位	是
材料 - 树脂	PPO
净重	0.293/g
行数	1
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.54mm

运行温度范围	-55° to +105° C
--------	-----------------

可配插/可连接使用的产品

可配插部件

描述	产品编号
C-Grid III Vertical Single Row Headers	<u>90120</u>
C-Grid III Single Row Headers	<u>90136</u>
C-Grid III Right-Angle Single Row Headers	<u>90121</u>

可连接使用部件

描述	产品编号
Pre-Crimped Lead C-Grid III Female-to-C-Grid III Female, Tin (Sn) Plating, 150.00mm Length, 22 AWG, Black	/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582022.html
Pre-Crimped Lead C-Grid III Female-to-C-Grid III Female, Tin (Sn) Plating, 300.00mm Length, 22 AWG, Black	/content/molex/molex-dot-com/cn/zh/products/product-page.html/797582023.html
C-Grid III Female Crimp Terminals	<u>90119</u>