



## 1032 LONER ATMOSCOPE SMT Hot Air Station

- Requires clean and dry shop air, 90 psi max
- Cost-effective
- Uses a wide variety of nozzles
- Adapts to foot switch operation
- Expands to include optional soldering iron
- Wide range of temperatures allows for:
  - Heating of shrink tubes
  - Fast shaping of plastics
  - Fast melting of glue
  - Touch up after flow soldering
  - Clearing solder bridges between circuit board etches



## 1036 LONER ATMOSCOPE Self-Contained SMT Hot Air Station

- Self-contained with built-in air source
- Zero voltage switching
- Uses a wide variety of nozzles
- Expands to include optional soldering iron
- Powerful 95 watt heater for larger components, up to 84 pins
- ESD-safe

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## TSX70 SOLDAVAC® SMT Reflow Vacuum Workstation

- Nitrogen can be used to reduce oxidation and bridging
- Dual controls for hot gas and tip temperatures to produce even heating of board
- Use for site preparation and reinstallation of QFP devices
- Recommended by major manufacturers and subcontractors in high volume BGA programs
- Perfect for solder bridge removal and fine pitch device reattachment

## Specifications for Model 1032



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage**  
**Leakage/Resistance**

### 1032-100

100V, 50Hz  
70W  
24V, 53W

### 1032-230

230V, 50Hz  
70W  
230V, 95W

### Options for 1032-230V

1032-230B  
British Standard Plug



1032-230P  
No Plug



1.4 kg

104 mm x 208 mm x 254 mm

205°C-427°C

< 2mV/< 2 ohms

±3°C

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Specifications for Model 1036



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage**  
**Leakage/Resistance**

### 1036-100

100V, 50Hz  
125W  
120V, 95W

### 1036-230

230V, 50Hz  
125W  
230V, 95W

### Options for 1036-230

1036-230B  
British Standard Plug



1036-230P  
No Plug



2.2 kg

132 mm x 216 mm x 254 mm

205°C-427°C

< 2mV/< 2 ohms

±3°C

## Specifications for Model TSX70



**Power Requirements**  
**Power Rating**  
**Heater Rating**

**Weight**

**Overall Dimension**

**Temperature Range**

**Temperature Regulation**

**Tip-to-Ground Voltage**  
**Leakage/Resistance**

### TSX70-100

100V, 50Hz  
39W - 330W  
24V, 70W  
24V, 45W

### TSX70-230

230V, 50Hz  
39W - 330W  
24V, 70W  
24V, 45W

### Options for TSX70-230

TSX70-230B  
British Standard Plug



TSX70-230P  
No Plug



3.1 kg

147 mm x 254 mm x 224 mm

205°C-427°C

< 2mV/< 2 ohms

±3°C