



ELECTRICAL CHARACTERISTIC			
(1)	INNER CONTACT RESISTANCE: <math>< 10m\ \Omega</math>		
(2)	OUTER CONTACT RESISTANCE: <math>< 2.5m\ \Omega</math>		
(3)	WITHSTAND VOLTAGE: DC1500V		
(4)	CURRENT RATING: 3A/DC1500V		
(5)	OPERATING TEMPERATURE: -30/+60°C		
5	SCREW	BRASS	
4	BODY	BRASS	
3	SHELL	Al	
2	BANANA PLUG	BRASS	
1	COPPER GRAIN	BRASS	
ITEM	DESIGNATION	MATERIAL	
REV	PART NO. & SAMPLE NO.	DATE	BY
A	1444		
B			

TOLERANCE	0 - 10 10 - 99 100 - 999 1000 - 9999 10000 - 99999	$\pm 0.05$ $\pm 0.5$ $\pm 10.0$ $\pm 100.00$ $\pm 1000.00$
-----------	--	--

SIGNATURES	DATE
DRAFT: ZHOU XIN GUO	11.01.10
CHECKED:	

SHEET	SCALE	UNIT	REV
OF	1:1	mm	$\emptyset$

TITLE	CUSTOMER
Can be use as Banana Plug or Jack	