

快速接頭連結器

Quick Splice Connectors



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

MAXIMUM ELECTRIC CURRENT:

A. W. G.	22	20	18	16	14	12
AMP.	3	4	7	10	15	20

MAXIMUM ELECTRICAL RATING: 105° C 600 VOLTS

INSULATION MATERIAL: NYLON

INSULATION COLOR:

22-18A. W. G. : RED

18-14A. W. G. : BLUE

12A. W. G. : YELLOW

TERMINAL MATERIAL: PHOSPHOR BRONZE

WIRE RANGE A. W. G. mm ²	ITEM NO.	Suggested Mate With Male Tab (Thickness X Width)	DIMENSION inch (mm)		FIGURE	COLOR	Q' TY BOX
			W	L			
22-18 A. W. G. 0.5-0.75 mm ²	☐ 878006	MDFNY1-250 (.032X.250)	0.386 9.8	1.457 37		RED	500
18-14 A. W. G. 0.75-2.5 mm ²	☐ 878106	MDFNY2-250 (.032X.250)	0.386 9.8	1.457 37		BLUE	500
12 A. W. G. 4 mm ²	☐ 878206	MDFNY5-250 (.032X.250)	0.386 9.8	1.457 37		YELLOW	500