



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

MAXIMUM ELECTRIC CURRENT:

A. W. G.	22	20	18	16	14	12	10
AMP.	3	4	7	10	15	20	24

MAXIMUM ELECTRICAL RATING: 75° C 600 VOLTS MAX.

INSULATION MATERIAL: VINYL

INSULATION COLOR:

22-16A. W. G. : RED 16-14A. W. G. : BLUE

12-10A. W. G. : YELLOW

DOUBLE CRIMP: WITH COPPER SLEEVE ON BARREL

TERMINAL MATERIAL: BRASS

TERMINAL BARREL I. D.:

22-16A. W. G. : C=1.7mm 16-14A. W. G. : C=2.3mm 12-10A. W. G. : C=3.4mm

WIRE RANGE A. W. G. mm ²	ITEM NO.	NEMA TAB	DIMENSION inch (mm)						FIG	Q' TY BOX
			W	F	L	B	D	T		
16-14 A. W. G.	<input type="checkbox"/> MPD2-156		0.157 4	0.335 8.5	0.854 21.7	0.413 10.5	0.185 4.700	0.016 0.4		1000
1.5-2.5 mm ²	<input type="checkbox"/> MPD2-180		0.177 4.5	0.354 9	0.854 21.7	0.413 10.5	0.185 4.700	0.016 0.4		1000
	<input type="checkbox"/> MPD2-195		0.197 5	0.335 8.5	0.835 21.2	0.413 10.5	0.185 4.700	0.016 0.4		1000