

End cover - D-ST 2,5-3L



3036660

<https://www.phoenixcontact.com/us/products/3036660>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

End cover, length: 99.5 mm, width: 2.2 mm, height: 50.3 mm, color: gray



勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3036660 |
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| Sales Key | B02 |
| Product Key | BE2Z1X |
| Catalog Page | Page 213 (C-1-2019) |
| GTIN | 4017918876609 |
| Weight per Piece (including packing) | 5.41 g |
| Weight per Piece (excluding packing) | 5 g |
| Customs tariff number | 85389099 |
| Country of origin | DE |

End cover - D-ST 2,5-3L



3036660

<https://www.phoenixcontact.com/us/products/3036660>

Technical Data

Product properties

| | |
|--------------|-----------|
| Product type | End cover |
|--------------|-----------|

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Material specifications

| | |
|---|-------------|
| Color | gray |
| Material | PA |
| Flammability rating according to UL 94 | V0 |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 27,5 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Dimensions

| | |
|--------|---------|
| Width | 2.2 mm |
| Height | 50.3 mm |
| Length | 99.5 mm |

End cover - D-ST 2,5-3L

3036660

<https://www.phoenixcontact.com/us/products/3036660>



勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力電子(上海) 86-21-34970699
勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27141133 |
| ECLASS-10.0.1 | 27141133 |
| ECLASS-11.0 | 27141133 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000886 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|