







Modular Terminal Blocks with Fixing Flange or Snap-in Mounting Foot 1.5 mm² / AWG 16, Series 260

| | | | |
|--|--|--|---|
| Test plug modules see page 10.28 | 0.08 – 1.5 mm² 400 V/6 kV/3 ① 18 A Terminal block width 5 mm / 0.197 in  8 – 9 mm / 0.33 in <small>* VDE KEA CCA KCC N S D P GL BV LR NV</small> | AWG 28 – 16 300 V, 10 A ② 300 V, 15 A ③ Terminal block width 8 mm / 0.315 in  8 – 9 mm / 0.33 in <small>* VDE KEA CCA KCC N S D P GL BV LR NV</small> | 2 x 0.08 – 1.5 mm² 2 x AWG 28 – 16 400 V/6 kV/3 ① 300 V, 10 A ② 18 A 300 V, 15 A ③ Terminal block width 8 mm / 0.315 in  8 – 9 mm / 0.33 in <small>* VDE KEA CCA KCC N S D P GL BV LR NV</small> |
|--|--|--|---|










勝特力電材超市-龍山店 886-3-5773766
 勝特力電材超市-光復店 886-3-5729570
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>



① 400 V = rated voltage
 6 kV = rated surge voltage
 3 = pollution degree
 (see also section 15)

| Description | Color | Item No. | Pack.-unit pcs | Color | Item No. | Pack.-unit pcs |
|---|------------------------------------|----------------|----------------|------------------------------------|----------------|----------------|
|  Terminal blocks with fixing flange, for screw fixing or similar methods, fixing hole diameter 3.2 mm (with mounting adapter 209-123 also for DIN 35 rail) | 2-conductor terminal blocks | | | 4-conductor terminal blocks | | |
| | grey | 260-301 | 300 (6 x 50) | grey | 260-331 | 300 (6 x 50) |
| | light grey | 260-303 | 300 (6 x 50) | light grey | 260-333 | 300 (6 x 50) |
| | blue | 260-304 | 300 (6 x 50) | blue | 260-334 | 300 (6 x 50) |
| | orange | 260-306 | 300 (6 x 50) | orange | 260-336 | 300 (6 x 50) |
|  Terminal blocks with snap-in mounting foot, for plate thickness 0.6 – 1.2 mm, fixing hole diameter 3.5 mm (fits aluminum rail 210-154 or with mounting adapter 209-120 for DIN 35 rail) | 2-conductor terminal blocks | | | 4-conductor terminal blocks | | |
| | grey | 260-311 | 300 (6 x 50) | grey | 260-341 | 300 (6 x 50) |
| | light grey | 260-313 | 300 (6 x 50) | light grey | 260-343 | 300 (6 x 50) |
| | blue | 260-314 | 300 (6 x 50) | blue | 260-344 | 300 (6 x 50) |
| | orange | 260-316 | 300 (6 x 50) | orange | 260-346 | 300 (6 x 50) |
|  End terminal block ③, without fixing foot, for terminal strips with snap-in mounting feet (see dimensioned drawings on page 10.19) | 2-conductor terminal blocks | | | 4-conductor terminal blocks | | |
| | grey | 260-321 | 300 (6 x 50) | grey | 260-351 | 300 (6 x 50) |
| | light grey | 260-323 | 300 (6 x 50) | light grey | 260-353 | 300 (6 x 50) |
| | blue | 260-324 | 300 (6 x 50) | blue | 260-354 | 300 (6 x 50) |
| | orange | 260-326 | 300 (6 x 50) | orange | 260-356 | 300 (6 x 50) |
| | green-yellow | 260-327 | 300 (6 x 50) | green-yellow | 260-357 | 300 (6 x 50) |

Accessories for modular terminal blocks and terminal strips (Marking accessories see section 14)

| | | | | | | |
|---|---|----------------|--------------|---|----------------|--------------|
|  End plate with fixing flange | grey | 260-361 | 100 (2 x 50) | grey | 260-361 | 100 (2 x 50) |
| | | | | | | |
|  End plate with snap-in mounting foot | grey | 260-371 | 100 (2 x 50) | grey | 260-371 | 100 (2 x 50) |
| | | | | | | |
|  Comb type jumper bar, insulated, 2-way | I _N 10 A | | | I _N 10 A | | |
| | grey | 260-402 | 25 | grey | 260-402 | 25 |
| | reduce wire to 1 mm ² /AWG 18 max. | | | reduce wire to 1 mm ² /AWG 18 max. | | |
|  Operating tool, insulated, for connecting the comb type jumper bar | 2-way | 209-132 | 1 | 2-way | 209-132 | 1 |
| | | | | | | |
|  Aluminum carrier rail, 1000 x 18 x 7 mm 3'3" x 0.709 x 0.276 in | | 210-154 | 1 | | 210-154 | 1 |
| | | | | | | |
|  Plastic end stop, with WSB marking facility, for aluminum rail 210-154 | 6 mm / 0.236 in wide | | | 6 mm / 0.236 in wide | | |
| | grey | 209-122 | 25 | grey | 209-122 | 25 |
|  Mounting adapter, for terminal blocks with snap-in mounting foot, for DIN 35 rail | 6 mm / 0.236 in wide | | | 6 mm / 0.236 in wide | | |
| | grey | 209-120 | 25 | grey | 209-120 | 25 |
|  Mounting adapter with screw, for terminal blocks with fixing flange, for DIN 35 rail | 6 mm / 0.236 in wide | | | 6 mm / 0.236 in wide | | |
| | grey | 209-123 | 25 | grey | 209-123 | 25 |
|  Mounting adapter for DIN 35 rail, can be used as end stop | 6.5 mm / 0.256 in wide | | | 6.5 mm / 0.256 in wide | | |
| | grey | 209-137 | 25 | grey | 209-137 | 25 |

*For further approvals with corresponding ratings see section 15.