

# Heavy-Duty PDU Power Cord, C13 to C14 - 15A, 250V, 14 AWG, 6 ft. (1.83 m), Black

MODEL NUMBER: P005-006



Computer power extension cord connects devices with C13/C14 power connectors or extends your existing power connection by 6 ft.

## Features

**C14-to-C13 Power Cable for Network Devices That Require a Heavy-Gauge Connection** This IEC-320-C14 to IEC-320-C13 cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. This C14 male to C13 female cord can be used to connect a computer, server, monitor or drive to a UPS system or PDU or replace or upgrade the standard power cord provided by the device's manufacturer. The 6-ft. (1.83 m) length allows you flexibility in placing equipment with respect to the power outlet.

## Highlights

- Recommended for powering computers, servers and other network devices
- 6-ft. (1.83 m) length allows flexibility in placing devices in relationship to AC outlet
- PDU-style cord replaces or upgrades standard power cord provided by manufacturer
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

## Applications

- Connect devices like computers, servers and monitors to a PDU up to 6-ft. (1.83 m) away in your data center
- Extend an existing power connection up to 6-ft. (1.83 m) to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer

## Package Includes

- P005-006 Heavy-Duty C13 to C14 PDU-Style Power Extension Cable, 6-ft. (1.83 m), Black

## Specifications

| OVERVIEW                    |   |
|-----------------------------|---|
| UPC Code                    | 037332150004  |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; Router; Network Switch; UPS; PDU |
| Country/Region              | Global  |
| INPUT                       |   |
| Maximum Input Amps          | 15  |
| Voltage Compatibility (VAC) | 100-250   |
| CONNECTIONS                 |   |
| Side A - Connector 1        | IEC-320-C14   |
| Side B - Connector 1        | IEC-320-C13   |



Powering Business Worldwide

勝特力電材超市-龍山店 886-3-5773766  
 勝特力電材超市-光復店 886-3-5729570  
 勝特力電子(上海) 86-21-34970699  
 勝特力電子(深圳) 86-755-83298787  
<http://www.100y.com.tw>

TRIPP LITE SERIES

| PHYSICAL                           |                                     |
|------------------------------------|-------------------------------------|
| Plug Color                         | Black                               |
| Cable Jacket Color                 | Black                               |
| Cable Jacket Material              | PVC                                 |
| Cable Jacket Rating                | VW-1                                |
| Power Cord Jacket Type             | SJT                                 |
| Cable Outer Diameter (OD)          | 9.3mm                               |
| Number of Conductors               | 3                                   |
| Wire Gauge (AWG)                   | 14                                  |
| Wire Gauge (OD - mm <sup>2</sup> ) | 2.08                                |
| Cable Length (ft.)                 | 6                                   |
| Cable Length (m)                   | 1.83                                |
| Shipping Dimensions (hwd / in.)    | 1.00 x 7.00 x 11.00                 |
| Shipping Dimensions (hwd / cm)     | 2.54 x 17.78 x 27.94                |
| Shipping Weight (lbs.)             | 0.78                                |
| Shipping Weight (kg)               | 0.35                                |
| Unit Dimensions (hwd / in.)        | 1.000 x 7.000 x 11.000              |
| ENVIRONMENTAL                      |                                     |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C)         |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C)         |
| Operating Humidity Range           | 10% to 65% RH                       |
| Storage Humidity Range             | 10% to 65% RH                       |
| FEATURES & SPECIFICATIONS          |                                     |
| Antibacterial                      | No                                  |
| Angled Plug                        | No                                  |
| High Voltage                       | Yes                                 |
| Locking Plug                       | No                                  |
| Coiled Power Cord                  | No                                  |
| STANDARDS & COMPLIANCE             |                                     |
| Product Certifications             | CSA (Canada); cUL Listed; UL Listed |
| Product Compliance                 | WEEE                                |
| WARRANTY & SUPPORT                 |                                     |