				REVISIONS			1
			REV ECO	DESCRIPTION	DATE	BY APPR	Í .
			A3 -	RELEASE NEW DWG FORMAT		DRP	
勝特力電材超市-龍山店 886-3-5773766			A4 C0540S	UPDATE DIMENSIONS		IONY TOMMY	
勝特力電材超市-光復店 886-3-5729570	- <u>^</u>		A5 -	ADD COLOR OPTION	-	OUIE TOMMY	
胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787 http://www.100y.com.tw		18.4					TITLE:
REQUIRES CONTACT RETENTION WEDGE AW3S		CAVITY "B"	CAVITY "A"				PLUG, 3 SOCKET, AT SERIES
NOTES: UNLESS OTHERWISE SPECIFIED			- CAVITY "C"		~		
<ol> <li>MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER</li> <li>MODIFICATIONS: N/A</li> <li>SPECIFICATIONS:</li> </ol>							DWG NO: AT06-3S-XXX
3.1 CURRENT RATING: 13 AMPS					$\backslash$		×
<ul> <li>3.2 OPERATING TEMPERATURE: -55°C TO +125°C</li> <li>3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.</li> <li>3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.</li> </ul>	28.6		ADDITIONAL CO	DARD MOLDED COLOR IS G LORS SHOWN IN PART NUN AVAILABLE VIA SPECIAL OR	iber <sup></sup>	-	REV: A5
3.5 MOISTURE RESISTANCE:	PART NUMBER CHART						ŝ
IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)	COLOR PART NUMB	ER					
3.6 MATING CYCLE DURABILITY: 100 CYCLES			SEE PART NUMBER CHAR	REF: DT06-3S, DT06-3S-E	004 DTDC 20 D012		9
3.7 RoHS COMPLIANT	GREY AT06-3S		PART NUMBER	DESCRIP		ITEM	
4. MATING PART: AT04-3P* RECEPTACLE	BLACK AT06-3S-BLK	QUANTITY					$\square$
(* = MODIFICATIONS AND COLORS )	BLUE AT06-3S-BLU	UNLESS OTHERS 1) All dimensions a			nhon		
	BROWN AT06-3S-BRN	2) Tolerances are a	In follows: LOUI	E 23NOV20	phen		
5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.	GREEN AT06-3S-GRN	2 PL DEC ±0.36 3 PL DEC ±0.08			is - www.amphenol-sine	a.com	ĺ
6\CONTACT SIZE AND REAR SEAL WIRE RANGE:	RED AT06-3S-RED	3) Note reference =		Clinton	Iorley Drive Fownship, MI 48036		1
	WHITE AT06-3S-WHT	MATERIAL SPECIFICAT	TIONS: CUSTOMER:				1
CONTACT MIN. INSUL MAX. INSUL TYPICAL SIZE O.D. O.D. WIRE RANGE	YELLOW AT06-3S-YEL			0.000	SOCKET, AT SEF	RES	l l
16         2.24 mm         3.68 mm         14 - 20 AWG           16         (.088 in)         (.145 in)         (2.0-0.5mm²)	ORANGE AT06-3S-ORG	PROCESS SPECIFICAT	THE AMPHENOL CORP OF REPRODUCTION A	RE IMPLIED. ALL BC-	AT06-3S-XXX	( A5	
		NEXT ASS'Y:	DIMENSIONS ARE SUB MANUFACTURING VAR	JECT TO NORMAL		1 OF 1	ļ

## A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

Machined Contacts, Sockets & Pins				
Part Number	Description	Size	AWG	Туре
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined

Tooling - Machined Contacts		
Part Number	Description	
AUTK-16	Hand Crimp Tool, Size 16	
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20	
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20	
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20	

Stamped & Formed Contacts, Sockets & Pins					
Part Number	Description	Size	AWG	Туре	
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-18	Stamped & Formed	
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-18	Stamped & Formed	
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-18	Stamped & Formed	
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-18	Stamped & Formed	
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed	
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed	
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed	
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed	
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	16-20	Stamped & Formed	
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	16-20	Stamped & Formed	
AT60-16-0644	Male Contact - Pin, Gold-plated	16	16-20	Stamped & Formed	
AT62-16-0644	Female Contact - Socket, Gold-plated	16	16-20	Stamped & Formed	
AT60-16-0677	Male Contact - Pin, Tin-plated	16	16-20	Stamped & Formed	
AT62-16-0677	Female Contact - Socket, Tin-plated	16	16-20	Stamped & Formed	
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed	
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed	
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed	
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed	

Tooling - Stamped & Formed Contacts		
MFX-3950	Crimp Die - Size 16, 18-20AWG	
MFX-3953	Crimp Die - Size 16, 16-18AWG	
MFX-3975	Crimp Die - Size 16, 14-16AWG	
MFX-3990	Crimp Die - Size 16, 20-22AWG	
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG	
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG	
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG	

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)			
Part Number	Description		
ATRT-100	Contact and Wedgelock Extraction Tool		
AT11-310-1605	Contact Removal Tool, Plastic, Size 16		

Sealing Plugs (For both Machined or Stamped & Formed Contacts)		
Part Number	Description	
A114017	Sealing Plug, Size 16, White	
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black	
AT13-217-1605	Locking Sealing Plug, Size 16, Grey	
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red	

Amphenol Sine Systems 44724 Morley Drive, Clinton Township, MI 48036 USA www.amphenol-sine.com 10-2023