



ELECTRICAL CHARACTERISTIC	
(1)	CONTACT RESISTANCE: $\leq 20\text{m}\Omega$
(2)	INSULATION RESISTANCE: $\geq 10\text{M}\Omega$
(3)	WITHSTAND VOLTAGE: DC300V
(4)	CURRENT RATING: 5A/DC150V
(5)	OPERATING TEMPERATURE: $-30^{\circ}\text{C} \sim 60^{\circ}\text{C}$

7	SHELL	ABS
6	COPPER PATCH	Cu
5	PLASTIC HANDLE	ABS
4	WASHER	Cu
3	EARTHING PATCH	Cu

2	NUT	Zn
1	BODY	Cu
ITEM	DESIGNATION	MATERIAL

TOLERANCE	SIGNATURES	DATE
0 - 10 ± 0.05 10 - 99 ± 0.5 100 - 999 ± 10.0 1000 - 9999 ± 100.00 10000 - 99999 ± 1000.00	DRAFT: cheng huan CHECKEO:	10.01.15

REV	PART NO. & SAMPLE NO.	DATE	BY
A	1354		
B			

APPROVAL:		SCALE	UNIT	REV
		1:1	mm	\emptyset
SHEET		OF		

TITLE	Binding Post, Medium (Red/Black) Gold
CUSTOMER	