

TRP-C36 Ethernet to RS-232/422/485 Isolated Converter



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Introduction

TRP-C36, a high speed, single-port serial device, is designed to instantly convert data from RS-232/422/485 interfaces to an Ethernet network running at the TCP/IP, UDP protocol. By using a standard COM port and existing network infrastructure the device allow you to link together a distant RS-232/422/485 serial device. You can reach TRP-C36 from Windows and Linux without the need to modify existing software. TRP-C36 supports 10/100Mbps auto-detecting, and auto RS-485 data direction flow control, it also provides with 3000V DC isolation and internal surge protection to protect the converter against high input voltage spikes and ground potential differences, and ensure a save data transmission on network. The industry standard DIN rail and panel mounting design enable user a fast and professional installation.

Features

- Wide input range DC power supply.
- Fully compatible with Ethernet TCP/IP protocol.
- Support 3000V DC isolation protection.
- Auto direction flow control on RS-485.
- Surge protection on RS-422/485 data lines.
- Support baud rate up to 230Kbps.
- Power/Link/TX /RX mode LED indicator.
- Support intranet and internet system setting function.
- Support screw terminal and standard external DC power adaptor.
- Operating System: Windows98/Me/2000/NT/XP.
- DIN rail and panel mount.

Specifications

- Power Input Voltage: DC +10V to +30V
- Interface: Standard RJ45 LAN port
- LAN: 10/100Base-T, 10/100Mbps auto-detecting.
- RS-232: 5 full-duplex (TXD, RXD, CTS, RTS, GND)
- RS-422: Differential 4 full-duplex wires (TX+ , RX+, TX- , RX-).
- RS-485: Differential 2 half-duplex wires (D+, D-)
- Connection type: Screw terminal, accepts AWG#12~30 wire.
- Signal LED: Power, Link, TX, RX
- Power supply: Screw terminal, or external DC adapter.
- Power consumption: 1.6W
- Isolation voltage: 3000V DC
- Operating environment: -10 to 50°C
- Storage temperature: -20 to 70°C
- Humidity: 10~90% Non-condensing
- Dimension: 151mm X 75mm X 26mm
- Weight: 375g

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)