

**DATA-SHEET**

Engineering

Printed On:  
2008/7/18**BRUSHLESS AXIAL COOLING FANS**

Customer	:		Ref. (RoHS)
Adda Model No	:	AD0912LS-A7BGL	
Samples attached	:	Piece(s),	
Safety Approval	:	CE	

**Specifications**

ITEM	SPECIFICATION / CONDITION
DIMENSIONS	: 90x90x25 MM
BEARING TYPE	: SLEEVE
RATED VOLTAGE	: 12.0 VDC
OPERATING VOLTAGE RANGE	: 10.8 VDC — 13.2 VDC
START-UP VOLTAGE	: 9.0 VDC, ( Duty 100% )
RATED /ACTUAL CURRENT	: 0.12 Amp. + 10% MAX / 0.09 Amp
RATED /ACTUAL POWER	: 1.44 Watt . / 1.08 Watt
RATED SPEED	: 2000 RPM $\pm$ 10 % ( IN FREE AIR AT RATED VOLTAGE )
AIR FLOW	: 38.0 CFM ( IN FREE AIR AT RATED VOLTAGE )
STATIC AIR PRESSURE	: 0.08 Inch Water ( IN FREE AIR AT RATED VOLTAGE )
NOISE LEVEL	: 27.5 dB (A)
MOTOR PROTECTION	: BY IC
CONNECTION LEAD TYPE	: WIRE, AWG#26
LIFE EXPECTANCY	: 30000 Hours at 40°C / 65%
NET WEIGHT	: 105 Gram.
PACKING	: 200 pcs. Per Export Carton.

\* If no PWM signal is present (no connection to the PWM drive signal) then the fan should run at maximum RPM.

\* The fan must start spinning with a 30% duty cycle or less.

Unless otherwise stated, the relative humidity is 65%, and the temperature is 40°C for the standard testing.

Should you have any doubt, please refer to the environmental conditions specified in the acknowledgement document.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

Model No.: AD0912LS-A7BGL

Page 1/4

## SPECIFICATION

### 1-0 SCOPE

- 1.1 If the information or other related document is inconsistent with this acknowledgement document, please refer to the acknowledge document.
- 1.2 This documentation defines the mechanical & electrical characteristics of DC brushless fans.
- 1.3 The specification of this product is described in details in the acknowledgement document. No guarantee is given to our product under the use of over specifications.
- 1.4 For any change or amendment to the specifications, such change will be noticed in writing beforehand.
- 1.5 If the product is used on the MIS system, please specify the specification in the purchase order.

### 2-0 MATERIAL

- 2-1 Frame : UL94V-0 Glass Filled polyester (P.B.T)  
2-2 Fan Blade : UL94V-0 Glass Filled polyester (P.B.T)

- 2-3 Bearing Sys. : (V) Sleeve, oil impregnated.  
( ) Two Ball Bearing  
( ) One Ball one Sleeve  
( ) Hypo Bearing  
( ) FDB Bearing

- 2-4 RoHS : (V) YES

### 3-0 DIMENSIONS & CONSTRUCTION

All dimensions, Direction of rotation and air flow were specified as per drawing attached.

### 4-0 CHARACTERISTICS & DEFINITION

- 4-1 All rated characteristics were specified as per data sheet enclosed.
- 4-2 Rated Current : Rated Current shall be measured after 3 minutes of continuous rotation at rated voltage.
- 4-3 Rated Speed : Rated Speed shall be measured after 3 minutes of continuous rotation at rated voltage.
- 4-4 Start Voltage : The voltage which is able to start the fan to operate by suddenly switching 'ON'.
- 4-5 Input Power : Input Power shall be measured after 3 minutes of continuous rotation at rated voltage.
- 4-6 Locked Rotor Current : Locked current shall be measured within one minute of rotor locked, after 3 minutes of continuous rotation at rated voltage in clean air.
- 4-7 Air Flow & Static Pressure : The air flow data and static pressures should be determined in accordance with AMCA standard or DIN24163 specification in a doublechamber testing with intake-side measurement.
- 4-8 Noise Level : The measurement of noise level is carried out with reference to CNS8753 in an anechoic chamber with the microphone positioned 1 meter from the air intake. Testing fan shall be hung in clean air.

#### NOISE LEVEL MEASUREMENT



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## SPECIFICATION

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### 5.0 MECHANICAL INSPECTION

#### 5.1 Rotation Direction

Counterclockwise when look into impeller side.

#### 5.2 Protection

All fans have integrated protection against locked rotor condition so that there will be no damage to winding or any electronic component.

Restarting is automatic as soon as any constraint to rotation has been released.

As fan placed at dead angle position, and the switch was changed from off to on. Restarting was automatic normal as soon as and proved that this fan is good fan.

#### 5.3 Locked Rotor Protection

No damage shall be found after 72 hours continuously at condition of rotation locked.

Restarting is automatic as soon as constraint to running has been released.

#### 5.4 Avoid the damage, check the correct voltage and proper polarity before connecting with power.

#### 5.5 Free Drop Shock

In minimum package condition, the fan should withstand drops on any three faces from a height of 30cm onto a wood board of 10mm thick.

#### 5.6 Please do not stick a grease and/or an oil to the fan housing or blade which may have a harmful influence by a chemical reaction at high humidity.

#### 5.7 If the fan is reinstalled, please pay special attention to the noise due to the vibration (or resonance).

#### 5.8 During the testing of the fan, please make sure the finger guard is used for safety.

### 6.0 ELECTRICAL INSPECTION

#### 6.1 Insulation Resistance

Not less than 10M ohm between housing and positive end of lead wire (red) at 500V DC.

#### 6.2 Dielectric Strength

No damage should be found at 500 VAC for 60 seconds, measured with 1mA trip current between housing and positive end of lead wire.

#### 6.3 Life Expectancy

The continuous duty life at given temperature after which, 90% of testing units shall still be running.

#### 6.4 While the fan is running, do not intentionally lock the fan for a long time since the overheating of the motor produced by the long-time locking will damage the fan.

### 7.0 ENVIRONMENTAL

#### 7.1 Improper use such as disassembling the fan, being covered with dust, or dipping the fan in water that results in defects is not covered in the warranty. Do not use the fan in the environment with corrosive air or liquid.

#### 7.2 Operating Temperature / Humidity

-10°C to +70°C at humidity 65%±20% RH.

#### 7.3 Storage Temperature

All function shall be normal after 500 hours storage at -40°C to +70°C with a 24 hour recovery period at room temperature.

#### 7.4 Humidity

After 96 hours, 95% RH, 40±2°C per MIL-STD-202F, method 103B humidity test, the measured data on insulation resistance and dielectric strength shall meet the specification.

#### 7.5 Do not place or store the fan in the environment with high/low temperature/humidity. Do not store the fan for over 6 months; even if the fan is stored in room temperature for over 6 months, the fan may have the electric current leakage.


## SPECIFICATION

### 8.0 REMARKS

- 8.1 Material and construction are subject to change without advance notice. The changes should be within specification.
- 8.2 All fans shall meet the quality inspection under sampling plan MIL-STD-105E as follow:

Critical	0.25%
Major	1.00%
Minor	2.50%

### 9.0 OUTLINE STYLING & DIMENSIONS



LEAD WIRES : UL 1061, AWG26, L =  $300 \pm 10$  MM  
Black = negative ; Red = positive  
White = FG ; Blue = pwm input

### 10.0 Notes:

- 10.1 Please do not touch and push Fan Blade with fingers or others, fan blade and sleeve bearings may be damaged and it causes noise defect.
- 10.2 Do not carry the fan by its lead wires.
- 10.3 If the fan does not have the polarity protection function, the connection of the colored wires should be Red + Red, and black + black, or else the fan will be damaged in no time.
- 10.4 For the models without reverse connection of polarity protection, please do not connect the lead wire in reverse


勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Model No. : AD0912LS-A7BGL


Page 4 / 4

PROVISION OF DIGITAL PWM SPEED CONTROL & LOCKED SIGNAL(F.G)  
 OUTPUT OF LOCKED SIGNAL-----OPEN COLLECTOR TYPE

(External signal function design is decided by customer)



- \*TRANSISTOR Q1 AT "ON" POSITION  
 COLLECTOR CURRENT----- $I_c = 10\text{mA MAX}$   
 SATURATION VOLTAGE----- $V_{\alpha} = 1\text{V MAX}$
- \*TRANSISTOR Q1 AT "OFF" POSITION  
 RELEASE VOLTAGE----- $V_{\text{on}} = 15\text{V MAX}$
- \*DIGITAL PWM SPEED CONTROL POSITION  
 PWM INPUT VOLTAGE HIGH----- $V_{\text{in}} = 5.5\text{V MAX}$   
 PWM INPUT VOLTAGE LOW----- $V_{\text{L}} = 0.5\text{V MAX}$
- \*PWM INPUT FREQUENCY-----FPWM:18KHZ~30KHZ



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)