

**60**mm sq.

# San Ace 60W

25mm thick(WP type)



## General Specifications With a pulse sensor

- Material ..... Frame: Plastics (Flammability: UL94V-0),  
Impeller: Plastics (Flammability: UL94V-1)
- Life Expectancy ..... Varies for each model (L10: Survival rate: 90% at 60°C, rated voltage, and continuously run in a free air state)
- Lead Wire ..... ⊕red ⊖black (Sensor) yellow
- Storage Temperature ..... -30°C to +70°C (Non-condensing)

**60×60×25mm** (Mass : 110g)

**IP 55** Dust resistant device with protection against water jets


**WP type**

## Specifications The numbers in ( ) represent ribless models.

Model No.	Rated Voltage [V]	Operating Voltage Range [V]	Rated Current [A]	Rated Input [W]	Rated Speed [min <sup>-1</sup> ]	Air Flow [m <sup>3</sup> /min] [CFM]		Static Pressure [Pa] [inchH <sub>2</sub> O]		SPL [dB(A)]	Operating Temperature [°C]	Life Expectancy [h]
9WP0612H401(4011)	12	10.2 to 13.8	0.11	1.32	3,800	0.53	18.7	40.2	0.161	28	- 10 to +70	60,000
9WP0624H401(4011)	24	20.4 to 27.6	0.06	1.44	3,800	0.53	18.7	40.2	0.161	28		
9WP0648H401(4011)	48	40 to 53	0.04	1.92	3,800	0.53	18.7	40.2	0.161	28		


Without Sensor   Pulse Sensor   Available in all models.   Lock Sensor   PWM Control   Please inquire as the availability of these functions depend on the model.

## Dimensions (Unit : mm) (With ribs)



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Reference dimension of mounting holes and vent opening (Unit : mm)





**Options (Unit : mm)**

**Finger guards**


Model : 109-139E Surface treatment : Nickel-chrome plating (silver)  
 : 109-139H : Cation electropainting (black)

**Resin Finger guards**


Model : 109-1003G



**Air Flow and Static Pressure Characteristics**



**9WP0612H401(4011)**  
**9WP0624H401(4011)**



**9WP0648H401(4011)**

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)