勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

TECHSPRAY™

Product Information

Genesolv® 2004

General Duty Defluxer

1616

Introduction

Genesolv® 2004 is an azeotropic solvent used for defluxing, precision cleaning or any application that requires the removal of organic and inorganic contaminates such as rosin-based fluxes, oils and similar contaminates found in electronics manufacturing.

Features / Benefits

Non-Flammable
Rapidly Evaporating

Physical Properties	
Boiling Point	30°C / 86°F
Flash Point (TCC)	None
Evaporation Rate	>1
Surface Tension	
Kauri-Butanol (KB Value)	

Chemical Components

Dichlorofluoroethane	(1717-00-6)	96%
Methanol	(67-56-1)	3.9%
Nitromethane	(75-52-5)	.1%
Carbon Dioxide (Propellant)	(124-38-9)	<3%

Plastic Compatibility

Material	Compatibility	Material	Compatibility
ABS	Not Compatible	**PMMA**	Not Compatible
Nylon	Excellent	**POM**	Excellent
Lexan	Not Compatible	**PP**	Excellent
HDPE	Excellent	**PS**	Not Compatible
CDPE	Excellent	**PTFE**	Excellent
C. E. Phenolic	Excellent	**PVC**	Excellent

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw

Packaging and Availability

Genesolv® 2004 may be ordered in the following container sizes:

1616-12S 12 Ounce Aerosol

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

TECHSPRAY

English MSDS
French MSDS
German MSDS
Italian MSDS
Spanish MSDS

Copyright 2003 Tech Spray, L. P.
For Commercial Use Only