

# WAT-902HB3s

1/3"

## 規格



- 超高感度
- 視頻光圈控制
- 低照度

首頁

系統:	EIA	CCIR
攝像素子 Pick-up element:	1/2" Interline transfer CCD image sensor	
總畫素:	811(H) * 508(V)	795(H) * 596(V)
有效畫素:	768(H) * 494(V)	752(H) * 582(V)
Unit cell size:	8.4um(H) * 9.8um(V)	8.6um(H) * 8.3um(V)
同步方式:	內同步	
掃描系統:	2:1 Internal	
信號輸出:	1Vp-p 75 Ω ( Unbalanced )	
水平解析度:	570TV lines	
最低照度:	0.0005Lux F1.4 (AGC HI)	
自動增益控制:	AGC (高:5~35dB, 低:5~32dB)	
信號雜訊比 S/N Ratio:	50 dB ( AGC off )	
Gamma 特性:	0.45	
背光補償:	ON	
電子光圈:	1/60~1/100000 (秒)	1/50~1/100000 (秒)
電子快門:	1/60(OFF), 1/100(FL) 1/250, 1/500, 1/1000 1/2000, 1/5000 (秒) 1/10000, 1/100000	1/50(OFF), 1/120(FL) 1/250, 1/500, 1/1000 1/2000, 1/5000 (秒) 1/10000, 1/100000
自動光圈:	視頻	
鏡頭座:	CS-MOUNT	
電源電壓:	DC + 12V +/- 10%	
消耗電流:	1.92W = (160mA)	
保存溫度:	- 30°C ~ +70°C	
動作溫度:	- 10°C ~ +40°C	
外觀尺寸:	40(W) * 20.7(H) * 40(L) mm	
重量:	約25g	
配件:	K-84 (電纜線), 六角螺絲刀	

