

圆筒帽形熔断体

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw



序号	熔断体型号				外形尺寸 / 尺码 (mm)		额定电压 (V)	额定电流 (A)	重量 (g)
	本公司		国内外同类产品						
	普通(gG)	快速(aR)	普通(gG)	快速(aR)	图号	φD × L			
0101	ROJ6	RS06	-	-	1.1	φ12.7 × 29	250/380	1~32	6.5
0102	ROJ7	RS07	-	-	1.1	φ30 × 57	600	10~100	75
0103	ROJ9	RS09	-	-	1.1	φ18 × 37	500	2~63	17.4
0104	ROJ10	RS10	-	-	1.1	φ18 × 50	500	2~63	23.5
0105	ROJ11	RS11	AJT JKS LPJ	ACL	1.1	φ21 × 58	600	2~32	51.5
0106	ROJ12	RS12	AJT JKS LPJ	ACL	1.1	φ27 × 60	600	35~100	90
0107	ROJ13	RS13	-	-	1.1	φ15 × 50	500	2~40	23.2
0108	ROJ14	RS14	RT19-16 gF1	-	1.1	φ8.5 × 31.5	500	0.5~20	4.4
0109	ROJ14A	RS14A	-	-	1.1	φ8.5 × 20	250	0.5~20	3.5
0110	ROJ14B	RS14B	-	-	1.1	φ8.5 × 36	380/500	0.5~20	5.0
0111	ROJ15	RS15	RT14-20 gF2 RT18-32 RT19-25	CTK KLM	1.1	φ10.3 × 38	380/500	0.5~32	7.7
0112	ROJ15A	RS15A	-	-	1.1	φ10.3 × 25.8	250	0.5~16	4.8
0113	ROJ15B	RS15B	-	-	1.1	φ10.3 × 31.5	250/500	0.5~25	5.8
0114	ROJ15C	RS15C	-	-	1.1	φ10.3 × 34	380/500	0.5~32	6.2
0115	ROJ15D	RS15D	-	-	1.1	φ10.3 × 37	600	2~32	11
0116	ROJ16	RS16	RT14-32 gF3 RT18-63 RT19-40	EWP	1.1	φ14.3 × 31	380/660	2~50	20.5
0117	ROJ16A	RS16A	-	-	1.1	φ14.3 × 38	500	2~50	15.6
0118	ROJ16B	RS16B	-	-	1.1	φ14.3 × 45	500	2~50	18.5
0119	ROJ16C	RS16C	-	-	1.1	φ14.3 × 37	500	2~50	27.5
0120	ROJ17	RS17	RT14-63 gF4 RT18-125 RT19-100	URE2263	1.1	φ22.2 × 58	380/660	10~125	58
0121	ROJ18	RS18	-	-	1.1	φ9.6 × 30	380	0.5~25	4.8
0122	ROJ19	RS19	FRS TRS FLSF	-	1.1	φ20.5 × 127	600	0.5~32	91.2
0123	ROJ19A	RS19A	FLNR PC2	-	1.1	φ20.5 × 76	250/500	0.5~63	63
0124	ROJ19B	RS19B	-	-	1.1	φ20.5 × 114	600	0.5~32	85
0125	ROJ19C	RS19C	FRS TRS FLSF	-	1.1	φ27 × 139	600	32~63	172.4
0126	ROJ19D	RS19D	-	-	1.1	φ27 × 147	600	32~63	160
0127	ROJ14	RS14	-	-	1.1	φ5 × 20	250	0.5~16	1
0128	ROJ15	RS15	-	-	1.1	φ5 × 25	250	0.5~16	1.3
0129	ROJ16	RS16	-	-	1.1	φ6 × 20	250	0.5~16	1.7
0130	ROJ17	RS17	-	-	1.1	φ6.3 × 25	250	0.5~16	2.1
0131	ROJ18	RS18	-	-	1.1	φ6.3 × 31.5	250/500	0.5~16	2.5
0132	ROJ18	RS08	-	JJS	1.2	φ20.5 × 40	600	2~63	40
0133	ROJ15T	RS15T	ATQR	CTK KLKR	1.3	φ10.3 × 38	380/600	0.5~32	7.5