

D-Fuse DII 25A gG 500V a.c./440 SENTRON fuse-link DIAZED size  
DII In 25A gG Un 500V a.c./440V d.c.

Model	
Product brand name	SENTRON
Product designation	DIAZED fuse
Design of the product	For cable and line protection
Design of the fuse link	DIAZED fuse link
General technical data	
Tripping characteristic class	Other
Size of fuse system / acc. to DIN EN 60269-1	DII
Operating class of the fuse link	gG
Diken-export / Let-through current	DS_5SB_DII_500_gG_25
circuit-breaker / Design	5SB2
Supply voltage	
Operating current / at AC / rated value	25 A
Supply voltage	440 V
• at DC	
Protection class	
Protection class IP	IP20, with connected conductors
Switching capacity	
Switching capacity current	8 kA
• at DC / acc. to IEC 60947-2 / rated value	50 kA
• acc. to IEC 60947-2 / rated value	
Dissipation	
Power loss [W]	3.4 W
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	3.4 W
Current	
Tripping residual / rated value / derated current / at 40 Cel	23.75 A
Diken-export / Let-through energy	DE_5SB_DII_500_gG_25
Appearance	
Color coding of the fuse link	yellow
Product details	
Product description	Using screw adapter or adapter sleeves

Mechanical Design	
Mounting position	Any, preferably vertical
Net weight	32 g

Environmental conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	-5 °C 40 °C
Ambient temperature / during storage	Air humidity 90% at 20 °C
Environmental category	Up to 45°C at 95 % rel. humidity

Certificates	
Reference code	
<ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to DIN EN 81346-2</li> </ul>	F F

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SB2811>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SB2811>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SB2811](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SB2811)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://www.siemens.com/specifications>

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

07/27/2020

Subject to change without notice  
© Copyright Siemens