

# TRM

Time-Delay Midget Fuses

MF

MIDGET, PC MOUNT & MINIATURE FUSES



Tri-Onic® TRM time-delay midget fuses are rated 250 volts AC and are offered in ampere ratings from 1/10 to 30A. They have 12 seconds time-delay at 200% rating to provide supplemental protection of small motors, small transformers and other high inrush loads, plus many other 250 volt applications. (Not for Branch Circuit Protection).

### FEATURES/BENEFITS:

- Numerous ratings for a wide variety of applications
- 250VAC rating in all sizes up to 30A
- Time-delay for circuits with high inrush current
- Can be used with UltraSafe™ fuse holders
- 1 1/2" x 13/32" (10mm x 38mm) dimensions

### CATALOG NUMBERS (AMPS)

TRM1/10	TRM4/30	TRM 1-1/8	TRM2	TRM3-2/30	TRM5-6/10	TRM8	TRM 15
TRM15/300	TRM1/2	TRM 1-1/4	TRM2-1/4	TRM3-1/2	TRM6	TRM9	TRM 20
TRM2/10	TRM6/30	TRM 1-4/10	TRM2-1/2	TRM4	TRM5-1/4	TRM10	TRM 25
TRM1/4	TRM8/30	TRM 1-6/10	TRM2-8/10	TRM4-1/2	TRM7	TRM12	TRM 30
TRM3/10	TRM1	TRM 1-8/10	TRM3	TRM5			

### RECOMMENDED FUSE BLOCKS for Midget (10x38mm) Fuses

Number of Poles	UltraSafe™ Indicating Fuse Holder	Catalog Number		
		Screw Connector	Pressure Plate Connector	Copper Box Connector
Addr		30310	3 0520	30350
1	USH11	30311	3 0521	30351
2	USH21	30312	3 0522	30352
3	USH31	30313	3 0523	30353
3	USF1101			

### RATINGS:

- Volts: 250VAC
- Amps: 1/30 to 30A
- I.R.: 10kA I.R.

### HIGHLIGHTS:

- Time-delay

### APPLICATIONS:

- Small motors
- Small transformers
- Lighting circuits
- Control circuits

### APPROVALS:

- UL listed to standard 248-14 File E33925
- CSA Certified to Standard C22.2 No. 248.14

