

Specs.	Voltage	Wattage	Luminous flux	Average life	Color temp.	Filament dimension	Max. overall length	Light center length	Max. bulb dia.	Base	ANSI code	Fig. No.
Lamp type	V	W	Lm	hrs.	°K	BxH	mm L <sub>1</sub>	mm L <sub>3</sub>	mm D			
JCD120V300WC	120	300	7,350	100	3,200	12.0x3.2	62.0	36.5	φ22.0	GY9.5 (2PP)	—	1
JCD120V300WCL	120	300	7,350	100	3,200	12.0x3.7	62.0	37.0	φ22.0	G6.35 (2PAGC)	—	2
JCD120V300WL	120	300	7,500	100	3,200	12.0x3.0	62.0	37.0	φ22.0	G6.35 (2PAGC)	—	2
JCD120V300WCP	120	300	7,500	100	3,200	12.0x3.0	62.0	37.0	φ22.0	G5.35 (2PAGC)	—	6
JCD120V500WL	120	500	12,500	70	3,200	13.0x5.0	62.0	37.0	φ22.0	G6.35 (2PAGC)	—	2
JCD120V500WC	120	500	12,500	70	3,200	13.0x5.0	62.0	36.5	φ22.0	GY9.5 (2PP)	—	1
JCD120V600WC	120	600	15,000	75	3,200	13.0x5.2	62.0	36.5	φ22.0	GY9.5 (2PP)	DYS	1
JCD120V600WC <sub>1</sub>	120	600	15,000	75	3,200	13.0x5.2	62.0	36.5	φ22.0	GY9.5 (2PP)	DYV	1
JCD120V600WCP	120	600	15,000	75	3,200	13.0x5.0	63.5	37.0	φ22.0	G5.35 (Min. 2-pin)	DYH	6
JCD120V600WM	120	600	16,200	80	3,400	10.0x4.2	53.0	37.0	φ22.0	—	DYP	3
JCD120V650WC	120	650	16,200	150	3,200	13.0x5.0	62.0	36.5	φ22.0	GY9.5 (2PP)	—	1
JCD120V650WL	120	650	16,200	150	3,200	13.0x5.0	62.0	37.0	φ22.0	G6.35 (2PAGC)	—	2
JCD120V650WSP	120	650	20,000	25	3,400	12.0x5.0	62.0	36.5	φ22.0	G5.35 (Min. 2-pin)	DVY	6
JCD220V650WC <sub>1</sub>	220	650	16,200	50	3,200	11.0x3.7	62.0	37.0	φ24.0	GY9.5 (2PP)	DYR	4
JCD220V650WL <sub>1</sub>	220	650	16,200	50	3,200	11.0x3.7	62.0	37.0	φ24.0	G6.35 (2PAGC)	—	5
JCD240V650WC <sub>1</sub>	240	650	16,200	50	3,200	13.0x3.6	62.0	37.0	φ24.0	GY9.5 (2PP)	DYR	4
JCD240V650WL <sub>1</sub>	240	650	16,200	50	3,200	13.0x3.6	62.0	37.0	φ24.0	G6.35 (2PAGC)	—	5
JCD120V1000WC	120	1,000	25,000	200	3,200	20.0x7.0	95.0	64.0	φ35.0	Medium 2-pin	—	7