



Halospot 70 50W BA15d 41990 fl



Manufacturer : Osram | Model : 004020

Nominal wattage 50W
Nominal voltage 12V
Rated wattage 50W
Power factor λ 1.00
Energy consumption 53 kWh/1000h

Nominal useful luminous flux 90° 510 lm
Light color as per EN 12464-1 Warm White
Luminous intensity 2600 cd
Beam angle 24 °
Color temperature 3000 K
Color rendering index Ra 100
Starting time 0.0 s
Warm-up time (60 %) 0.00 s
Lumen main.fact.at end of nom.life time 0.75
Rated useful luminous flux 90° 510 lm

Diameter 70.5 mm
Overall length 45.6 mm
Outer bulb AR70
Length 50.0 mm
Maximum diameter 71.0 mm

Lamp mercury content 0.0 mg
Mercury-free Yes

Nominal lamp life time 2000 h
Rated lamp life time 2000 h
Number of switching cycles 75000

Base (standard designation) BA15d

Burning position Any
Dimmable Yes

Energy efficiency class C

Presenting things in a better light. Thanks to their excellent spotlighting and extremely high luminous intensity HALOSPOT 70 from OSRAM are real professionals when it comes to presenting rooms and objects in their best light. The faceted reflector ensures the light is evenly distributed. With HALOSPOT lamps there is no need to worry about heat building up in suspended ceilings because the aluminum reflector ensures that most of the heat is emitted forwards.

Product benefits

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Excellent distribution of light thanks to faceted reflector
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in fixture thanks to aluminum-coated reflector
- Contains no mercury, can be thrown away with normal household waste

Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)