

Special lamps.

OSRAM lamp technology in the service of industry. Light is now used in a very wide range of industries as a technically, economically and ecologically superior alternative to conventional processes. It is used, for example for:

- curing
- drying
- thermo-forming
- · artificial material aging
- sterilizing

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw

There are also a number of classic industrial applications for light which would be impossible without these special lamps. These include:

- exposure of printing plates
- exposure of photo-resist material in the manufacturing process of printed circuit boards

WWW.100Y.COM.TW

• fluorescence excitation for material analysis

Contents.

MY.COM.TW

1.100

W.100Y.CO.

ULTRA-VITALUX® UV high-pressure lamps	6.
EVERSUN® UV fluorescent lamps for solariums and sun beds	6.0
ULTRAMED® UV high-pressure lamps	6.0
OSRAM DULUX® BLUE / OSRAM DULUX® BLUE UVA	6.0
PURITEC® HNS® germicidal lamps producing no ozone	6.0
Bases, burning positions	6.1

WWW.100Y.COM.TW

NW.100X.COM.1 V

COM.TW

WI.MI

COM.TW

L.COM.TW



HALOTHERM®

Product reference	Product number	A	W	VK	[h] 1)	(2)
HALOTHERM® infrare	d halogen lamp					
Quartz clear						
ITT 700/235-0170	4008321 203533	3,0	700	235 2350 50	000 p15	R7s
Product reference		A	Ø [mm]	I max. [mm]		No.
ITT 700/235-0170		6,3f	10	251 170	12	4

HALOTHERM®


HALOTHERM® lamps are infrared halogen lamp developed specially for technical applications. Halogen additives prevent bulb blackening and ensure long life. Maximum radiation is in the shortwave infrared range (IR-A) at around 1100 nm. By using quartz that is highly transparent for infrared radiation the thermal output is emitted in the shortwave infrared range with minimal losses. The main benefits of the HALOTHERM® lamps compared with other methods such as hot air or black-tube radiant heaters are their short response time, precise controllability and high efficiency. Lamps with integrated aluminum oxide reflectors considerably increase the radiated power on the surfaces to be heated, particularly over short distances.

HALOTHERM® lamps are used in various processes in the plastics, paper and printing industries, for drying paint, for keeping food warm in restaurants and in modern heat lamps.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw

WW.100Y.C

SICCATHERM® infrared heat lamps



Product reference	Product number	W	V		t [h]		
SICCATHERM® infrared he	eat lamps						
SICCA R125 FR 250W	4050300 014029 ²)	250	230	Frosted	5000	s180	30
SICCA R125 CL 375W	4050300 206912	375	230	Clear	5000	s180	30
SICCA PAR38 Red 175W	4050300 010991	175	230	Red filter	5000	h90	30
SICCA PAR38 Red 250W	4050300 206998	250	240	Red filter	5000	S180	30
SICCA PAR38 CL 250W	4008321 178084	250	240	Clear	5000	S180	30
Product reference		1):	3) d [mm]	I ma	- ~	a	No.
SICCA R125 FR 250W	MAN 100X	E27	127	185	10	12	2
SICCA R125 CL 375W		E27	127	185		12	2

E27

E27

E27

Please note:

SICCA PAR38 Red 175W

SICCA PAR38 CL 250W

SICCA PAR38 250W

Considerable heat is produced. Operate the lamps only in suitable fixtures. All the lamps labeled 2) are splash-proof.

SICCATHERM® infrared lamps are used not only for drying paints and varnishes, for various burn-in processes and for keeping food warm in restaurants, they are also used in industry for pasteurizing, polymerizing, vulcanizing and distilling. In agriculture, SICCATHERM® infrared lamps are used for raising young animals and the intensive drying of agricultural products.

How the lamps work in raising animals:

Animals typically grow faster owing to their greater appetite and improved extraction of nutrients in their fodder. They develop increased resistance to disease and no longer crowd together for warmth. Breeding losses are therefore reduced. Hay remains dry and stalls stay clean and hygienic for longer. This increases the efficiency of the entire livestock operation. These infrared lamps are also used for varnish and paint curing, burn-in processes and distillation.

136

185

185

12

12

12

1

How the lamps work in drying:

122


127

127

The infrared radiation penetrates the material to be dried and is absorbed by it. There is virtually no heat dissipated to the surrounding air. The advantage is that the entire material is heated, not just the surface. The drying process is so efficient that it is equivalent to enlarging the evaporation area several times over.

SICCATHERM® lamps are also used in food processing for pasteurizing and drying, and for keeping food warm.

THERATHERM® infrared heat lamps



E27

122

136

12

2

Please note:

Considerable heat is produced. Operate the lamps only in suitable fixtures.

THERATHERM®

THERA PAR38 Red 150W

THERATHERM® infrared heat lamps emit short-wave radiation in the infrared range. A specially pigmented red filter gives the lamp a pleasant and even glow. The parabolic internal reflector focuses the radiated energy into a high-intensity beam. The lamps switched on and have a very high life expectancy.

THERATHERM® lamps are used with great success for cosmetic beauty treatment and also as heat sources over relaxation areas in swimming pools and saunas.

¹⁾ E27 base to IEC 60061-1 2) Protect the lamp against moisture and splashes 3) Max. base temperature 250 °C to EN 60240-1





Product reference	Product number	W	V	t [h] 2)		
ULTRA-VITALUX®	WWW.100 Y.COM	TW V	VWW.10	OOX.CON	MTW	
ULTRA VITALUX	4050300 003 3	313 300	230	1000	universal	E27
Product reference		UVA/W	UVB/ W	d [mm]	I max.	7
ULTRA VITALUX		13,61)	3,01)	127	185	6

Please note:

Because of the intense heat produced the lamps should be operated only in suitable fixtures. Protect the lamps against moisture and splashes. If used incorrectly, UV radiation may lead to sunburn and conjunctivitis. This unit is not a medical product. You should consult your doctor if you have any medical problems. Only your doctor will be able to suggest suitable treatment for your symptoms.

ULTRA-VITALUX®

The ULTRA-VITALUX® lamp produces a mix of radiation very similar to that of natural sunlight and can have the same positive effects on the body as the sun. This blend of radiation is generated by a quartz discharge tube and a tungsten filament. The bulb is made of special glass which allows only that part of the output that is contained in natural sunlight to pass through.

ULTRA-VITALUX® lamps are suitable for technical applications such as curing special adhesives and plastic and sunlight simulation in industrial material testing. ULTRA-VITALUX® lamps can also be used for the exposure of UV-sensitive photoresist coatings. Other areas of application include wellness, terrariums and equine solaria.

EVERSUN® UVA fluorescent lamps for solariums and sun beds





Product reference	Product number	W	t [h]	UVA W	UVB/ W	d [mm]	max. [mm]	4
EVERSUN® UVA fluo	orescent lamps for solari	ums and su	ın beds					
L 40/79 K ²⁾	4050300 015873	40	500	8,1	0,06	38	590	25
L 100/79	4050300 016955	100	500	31,0	0,25	38	1760	25
L 100/79 SUPER	4050300 019185	100	800	27,0	0,38	38	1760	25

Please note:

Correct operation is only guaranteed if the lamps are used in equipment specially designed for them.


They should therefore be installed only by the manufacturers of such equipment.

EVERSUN® lamps emit high-intensity UV radiation that can cause sunburn and conjunctivitis.


Ballasts are available from leading manufacturers.

EVERSUN® lamps were developed especially for use in solariums and sun beds. They are available in three versions depending on the desired effect:

- EVERSUN® 79 and 79 R with high UVA emittance for direct pigmentation and a low UVB component for creating new pigment. This UVB component is very low, however, so the danger of sunburn is very low.
- EVERSUN® SUPER with a sun-like effect thanks to the high UVA component and balanced proportion of UVB radiation. Strict adherence to a suntanning schedule will result in durable pigmentation, a fresh and long-lasting holiday tan and a high safety factor for the skin.







ULTRAMED® UV metal halide lamps ULTRAMED 400 4050300224114 400 230 R7s 88 8 14 104¹¹) 33 25 1	Product reference	Product number	W	V		UVA/W	UVB/ W	d [mm	max. [mm]	a [mm]		No.
ULTRAMED 400 4050300 224114 400 230 R7s 88 8 14 104 ¹⁾ 33 25 1	ULTRAMED® UV n	netal halide lamps										
	ULTRAMED 400	4050300 224114	400	230	R7s	88	8	14	1041)	33	25	1

Please note:

Correct operation is only guaranteed if the lamps are used in equipment specially designed for them.

They should therefore be installed only by the manufacturers of such equipment.

ULTRAMED® lamps emit high-intensity UV radiation that can cause sunburn and conjunctivitis.

The skin and eyes must therefore not be exposed to direct or reflected unfiltered radiation.


Owing to the high radiation intensity in the ultraviolet range from 280 to 400 nm range achieved by the use of special filler substances, these high-quality high-intensity UV lamps can be used with various filters and reflectors. The efficiency of such systems is then very high.

Suitable filters must be used for the cosmetic applications mentioned above. The entire ULTRAMED® range has been granted FDA approval.

Applications:

- The high radiation intensity in the UVA range encourages tanning through direct pigmentation.
- A balanced proportion of UVB radiation helps form new pigmentation to achieve a lasting tan, depending on skin type.


勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-54151736 胜特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw



1) Distance between contacts

OSRAM DULUX® BLUE & BLUE UVA PURITEC® HNS® germicidal lamps producing no ozone





Product reference	Product number	W		UVA/W	max.	I1 [mm]	4	No.
OSRAM DULUX® BLUE								
DULUX S BLUE 9W/71 ¹⁾	4008321 198860	9	G23	= X	167	144	50	1
DULUX L BLUE 18W/71 ²⁾	4008321 198884	18	2G11	JA A	217	7.0	10	2
OSRAM DULUX® BLUE UVA								
1. 1. 1. 1. 1. 1. 1.	1007.0	OMITY		W.	- TOW 1	00x	$T.M_{\Omega}$	N 1
DULUX S BLUE UVA 7W/78	4008321 198907	07	G23	1,2	137	114	50	
DULUX S BLUE UVA 9W/78	4008321 198938	9	G23	1,5	167	144	50	1 _W
DULUX S BLUE UVA 11W/78	4008321 198969	_11M	G23	1,8	237	214	50	1
DULUX L BLUE UVA 18W/78	4008321 198990	18	2G11	3,0	217	N -1 00	10	2


OSRAM DULUX® BLUE

OSRAM DULUX® BLUE compact fluorescent lamps are approved for use in medical applications. They are also used for polymerization of blue-sensitive plastics, adhesives, paints and dyes.

OSRAM DULUX® BLUE UVA

OSRAM DULUX® BLUE UVA compact fluorescent

lamps are used for curing plastics, sealing surfaces in dentistry, insect traps, as a UV light source for circuit board manufacture, in terrariums and as a fluorescence exciter for scientific investigations. Using a black glass filter to improve contrast, these lamps can also be used for real-time verification of banknotes and credit cards.




Product reference	Product number	Α	W	Luvc E	d [mm] a [mm]		No.
PURITEC® HNS®	germicidal lamps produ	icing no	ozon	e 10			
G23 base							
HNS S 9W G23	4050300 941226	0,17	9	2,5 G23	27 165 123	50	1/1

Please note:


PURITEC® HNS® lamps emit high-intensity UV radiation that can cause sunburn and conjunctivitis. The skin and eyes must therefore not be exposed to direct or reflected unfiltered radiation.

PURITEC® HNS® compact lamps


PURITEC® HNS® compact lamps are suitable for disinfecting water eg. ponds and aquariums. They also provide a reliable service for pure water systems and water dispensers. Air purification applications include air-conditioning systems and refrigerators. They are also used for disinfecting surgical instruments.



Bases IEC/EN 60061-1



Burning position Schematic diagram



s = standing (base down)

h = hanging (base up)

p = horizontal (base at the side)

Permitted angle: The number after the letter for the main burning position indicates the permitted angle of deviation from the main burning position in degrees.