

EAN/ Product: 4050300018423
Product description: DULUX L 18W/954 2G11 10X1 **DULUX L 18W/954 2G11 FS1**

General Description	
Sstl-Number	4933502
Base (standard designation)	2G11
Technical - Electrical Data	
Nominal wattage (packaging)	18 W
Technical - Geometries	
Diameter	17.5 mm
Construction length	223.30 mm
Technical - Light Technical Data	
Light colour	954

勝 特 力 材 料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Packaging units				
EAN	Packaging unit Pieces/ Unit	Dimensions in h x w x l	Gross weight	Volume
4050300018423	Folding carton box (contains 1 Piece)	25,000 mm x 48,000 mm x 244,000 mm	0,075 kg (0,065 kg)	0,293 Cubic dec.
4050300251608	Shipping carton box (contains 10 Piece)	260,000 mm x 145,000 mm x 260,000 mm	1,063 kg (0,650 kg)	9,802 Cubic dec.

system overview												
operation of lamp with	Length in mm	Number of lighting outlet	Length in mm	Width in mm	Height in mm	System power consumption in W (ECG)	System power consumption in W (CCG)	System power consumption in W (LLB)	Luminous flux with ECG in lumen	Luminous flux in lumen (CCG)	Power factor	
HF 1x18/230-240 DIM	217 / 122 mm	1	360 mm	30 mm	30 mm	19 W	30 W	29 W	1150 lm	1200 lm	0.96	
QT 1x18/230-240	217 / 122 mm	1	237 mm	30 mm	30 mm	20 W	30 W	29 W	1200 lm	1200 lm	1	
HF 2x18/230-240 DIM	217 / 122 mm	2	423 mm	30 mm	30 mm	36 W	46 W	44 W	2 * 1150 lm	2 * 1200 lm	0.96	
QT 2x18/230-240	217 / 122 mm	2	237 mm	42 mm	30 mm	40 W	46 W	44 W	2 * 1200 lm	2 * 1200 lm	1	
QTi 1x14/24/21/39	217 / 122 mm	1	360 mm	30 mm	21 mm	20 W	30 W	29 W	1150 lm	1200 lm	0.96	
QT-ECO 1X18-24/220-240 S	217 / 122 mm	1	80 mm	40 mm	22 mm	18 W	30 W	29 W	1100 lm	1200 lm	0.92	
QT-ECO 1X18-24/220-240 L	217 / 122 mm	1	150 mm	22 mm	22 mm	18 W	30 W	29 W	1100 lm	1200 lm	0.92	
QTi 2X14/24/21/39	217 / 122 mm	2	423 mm	30 mm	21 mm	40 W	46 W	44 W	2 * 1150 lm	2 * 1200 lm	0.96	
QTi DALI 1X18 DIM	217 / 122 mm	1	360 mm	30 mm	21 mm	19 W	30 W	29 W	1150 lm	1200 lm	0.96	
QTi DALI 2X18 DIM	217 / 122 mm	2	423 mm	30 mm	21 mm	38 W	46 W	44 W	2 * 1150 lm	2 * 1200 lm	0.96	
HF 3x18/230-240 DIM	217 / 122 mm	3	425 mm	39 mm	28 mm							
HF 4X18/230-240 DIM	217 / 122 mm	4	425 mm	39 mm	28 mm							
QT-M 1X26-42/230-240	217 / 122 mm	1	103 mm	67 mm	31 mm	18 W	30 W	29 W	1150 lm	1200 lm	0.97	
QT-M 2x26-32/230-240	217 / 122 mm	2	123 mm	79 mm	33 mm	35 W	46 W	44 W	2 * 1150 lm	2 * 1200 lm	0.96	