

5 W (3 ~ 16V) A C - D C S W I T C H I N G A D A P T O R

ORDERING INFORMATION

Model	Output Rating	Tol.	R&N	Pmax.
JLD-0305W	3V/1.00A ±50mA	8%	50mV	5W
JLD-0405W	4V/1.00A	8%	50mV	5W
JLD-0505W	5V/1.00A	8%	60mV	5W
JLD-0605W	6V/0.83A	8%	60mV	5W
JLD-1205W	12V/0.42A	8%	120mV	5W

特殊規格可訂製3.3V 4.2V 4.5V 7.5V 9V 15V等

FEATURE

- Compact size , light weight
- Over load protection
- DC output plug option
- Short circuit protection
- Low cost / high reliability
- 100% full load burn-in test
- 1 year warranty

美規



歐規



ELECTRICAL SPECIFICATIONS


Input

Input range----- 100 – 240VAC(Full Range) , 47 – 63Hz
Input current (rms)--- 160mA @ 90VAC; 80mA @ 260VAC MAX.
Efficiency ----- >70% @ full load, 115VAC (DC Conversion)
EMI ----- FCC , part 15 , class B
EN61000-4-2 , 3 , 4 , 5 , 6 , 11 ,
EN 55022

Output

Voltage (Vo) ----- +3V ~ +16V
Voltage regulation --- ±8% @ constant voltage mode
Current limit ----- ±8% @ constant current mode
Maximum power (Po) ----- 5W
Setup , hold-up time----- 800ms , 8ms @ full load and 115VAC
Protection ----- Over voltage protection (OVP),AC recycle
Short circuit protection; Output short circuit protection (<0.03 ohm)
Pulsing mode , auto recovery

Body size ----- 46 x 35 x 24 mm

Length of output cable ----- 150 cm , AWG 22 X 2C 

Standard plug of DC output ----- As your instruction

SAFETY

UL 1950
TUV EN60950
CE EMC

ENVIRONMENTAL

Operating temperature----- 0°C to +40 °C ambient
Storage temperature ----- -10 °C to +60 °C
Humidity ----- 20% ~ 90% RH

勝特力材料 886-3-5753170

胜特力电子(上海) 86-21-54151736

胜特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)