

規格比較

勝特力電材超市-龍山店 886-3-5773766
 勝特力電材超市-光復店 886-3-5729570
 勝特力電子(上海) 86-21-34970699
 勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>

		GPE-100W		GPS-Series			
		GPE-1323	GPE-1205	GPS-3030DD	GPS-3030D	GPS-1830D	GPS-1850D
Channels		CH1	CH1	CH1	CH1	CH1	CH1
Output	Voltage	32.000V	20.000V	30.0V	30.0V	18.0V	18.0V
	Current	3.0000A	5.0000A	3.00A	3.00A	3.00A	5.00A
	Power	96W	100W	90W	90W	54W	90W
Tracking Function	Series	64V/3A	40V/5A	--	--	--	--
	Parallel	32V/6A	20V/10A	--	--	--	--
Line regulation	Voltage	≤ 0.01%+3mV		≤ 0.01%+3mV			
	Current	≤ 0.2%+3mA		≤ 0.2%+3mA			
Load regulation	Voltage	≤ 0.01% + 3mV (≤ 3A)		≤ 0.01% + 3mV (≤ 3A)			
		≤ 0.01% + 5mV (> 3A)		≤ 0.01% + 5mV (> 3A)			
	Current	≤ 0.2%+3mA		≤ 0.2%+3mA			
Ripple & Noise	Constant Voltage	≤ 0.5mVrms		≤ 0.5mVrms (≤ 3A), ≤ 1mVrms (> 3A)			
	Constant Current	≤ 2mArms		≤ 3mArms			
Setting / Readback Resolution	Voltage Resolution	1mV / 0.1mV		10mV (≤18V) / 100mV (≥20V)			
	Current Resolution	0.1mA / 0.01mA		1mA (<2A) / 10mV (≥2A)			
Recovery Time		≤100us		≤100us			
Protection		OVP, OCP, OTP, reverse		Overload, reverse			
Features	Display	2.4" TFT LCD		3 1/2 digits 0.39" LED	3 1/2 digits 0.5" LED		
	Inter-channel isolation	●			●		
	Key lock	●			--		
	Intelligent cooling fan	●			--		
	Power ON/OFF state setting	●			--		
	Remote sense	●			--		
	EXT I/O control	For Series / Parallel Function			●		
Dimensions & Weight	Dimensions	107(W) x 124 (H) x 313 (D) mm		128 (W) x 145 (H) x 285 (D) mm			
	Weight	5.5kg		5kg	5kg	4kg	5kg
Power	AC input	AC 100V/120V/220V/240V±10%, 50/60Hz		100V/120V/220V/240V±10%, 50/60Hz			
		替代機種		GPE-1323	GPE-1323	GPE-1205	GPE-1205

替代機種

GPE-1323

GPE-1323

GPE-1205

GPE-1205