

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

型号	KPS1610	KPS3205	KPS6003	KPS1620	KPS3010	KPS6005
输出电压范围	0-16V	0-32V	0-60V	0-16V	0-30V	0-60V
输出电流范围	0-10A	0-5A	0-3A	0-20A	0-10A	0-5A
效率(220Vac, 满载)	≥86%	≥87%	≥88%	≥87%	≥88%	
满载输入电流(220Vac)	≤1.5A	≤1.4A	≤1.5A	≤2.5A	≤2.4A	≤2.3A
空载输入电流(220Vac)	≤100mA	≤80mA	≤100mA	≤120mA		
电压表精度	≤0.3%+1digit					
电流表精度	≤0.3%+2digits			≤0.3%+3digits		
恒压状态						
负载调节率(0-100%)	≤50mV	≤30mV	≤50mV	≤30mV		
输入电压调节率(198-264Vac)	≤10mV					
纹波噪音(Peak-Peak)	≤30mV	≤50mV	≤30mV	≤50mV		
纹波噪音(r.m.s)	≤3mV	≤5mV	≤3mV	≤5mV		
设置精确度	≤0.3%+10mV					
瞬间响应时间(50%-10% Rated Load)	≤1.0ms					
恒流状态						
负载调节率(90%-10% Rated Voltage)	≤50mA			≤100mA		
输入电压调节率(198-264Vac)	≤10mA	≤20mA	≤10mA	≤50mA	≤20mA	
纹波电流噪音(峰-峰值)	≤30mA _{p-p}			≤100mA _{p-p}	≤50mA _{p-p}	
设定精确度	≤0.3%+20mA					
工作电压范围	110/220±10%Vac					
工作频率范围	45-65HZ					
尺寸(宽×高×深)	120×55×168mm			120×55×240mm		
净重	0.75KG			1.0KG		

产品外观 Product appearance

01

KPS3205/1610/6003
 3010/1620/6005
 正面、背面





KPS3205/1610/6003尺寸



KPS3010/1620/6005尺寸



02

KPS6011/6017/1660/3232/3220 正面、背面及尺寸

