

Redundancy module, with protective coating - QUINT-DIODE/40 - 2938963



Redundancy module QUINT-DIODE/40



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Key commercial data

Packing unit	1 pc
GTIN	
Weight per Piece (excluding packing)	700.0 g
Weight per piece (including packing)	684.0 g
Custom tariff number	85049091
Country of origin	China
Sales Key	H1 - Power supply units

Technical data

Dimensions

Width	62 mm
Height	84 mm
Depth	102 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C (> 60 °C derating, # -25 ... 60°C)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Max. permissible relative humidity (operation)	≤ 95 % (at 25 °C, non-condensing)
Noise immunity	EN 61000-6-2:2005

Input data

Redundancy module, with protective coating - QUINT-DIODE/40 - 2938963

Technical data

Input data

Nominal input voltage	24 V DC
Input voltage range	0 V DC ... 30 V DC
Nominal input current I_N	2x 20 A (Max. 30 A)
	1x 40 A (Max. 60 A)
Maximum current I_{max}	2x 19 A (6 mm ² at 40°C)
	1x 39 A (6 mm ² at 40°C)
	2x 16 A (6 mm ² at 60°C)
	1x 32 A (6 mm ² at 60°C)
	2x 27 A (10 mm ² at 40°C)
	1x 54 A (10 mm ² at 40°C)
	2x 21 A (10 mm ² at 60°C)
	1x 43 A (10 mm ² at 60°C)
	2x 30 A (16 mm ² at 40°C)
	1x 60 A (16 mm ² at 40°C)
	2x 24 A (16 mm ² at 60°C)
	1x 48 A (16 mm ² at 60°C)

Output data

Nominal output voltage	24 V DC
Output current	40 A
Power loss nominal load max.	20 W

General

Net weight	0.7 kg
Efficiency	> 97 %
Insulation voltage input/output	1 kV
Protection class	II (in closed control cabinet)
Mounting position	horizontal and vertical DIN rail NS 35, EN 60715
Assembly instructions	Can be aligned: Horizontal 2 cm, vertical 5 cm
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 55011
Declaration of conformity in acc. with EN 60079-15	# II 3 G Ex nA II T4 X
ATEX	# II 3 G Ex nA II T4
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Shipbuilding approval	Germanischer Lloyd (EMC 2), ABS, DNV
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL/C-UL listed UL 508
	UL/C-UL Recognized UL 60950
	UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D

Redundancy module, with protective coating - QUINT-DIODE/40 - 2938963

Technical data

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	10 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Stripping length	10 mm
Screw thread	M4

Connection data, output

Connection method	Screw connection
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section stranded min.	0.5 mm ²
Conductor cross section stranded max.	10 mm ²
Conductor cross section AWG/kcmil min.	20
Conductor cross section AWG/kcmil max	6
Stripping length	10 mm

Classifications

eCl@ss

eCl@ss 4.0	27040702
eCl@ss 4.1	27040702
eCl@ss 5.0	27242213
eCl@ss 5.1	27242213
eCl@ss 6.0	27049005
eCl@ss 7.0	27049005
eCl@ss 8.0	27049002

ETIM

ETIM 2.0	EC001039
ETIM 3.0	EC001039
ETIM 4.0	EC000599
ETIM 5.0	EC002540

UNSPSC

UNSPSC 6.01	30211502
UNSPSC 7.0901	39121004

Redundancy module, with protective coating - QUINT-DIODE/40 - 2938963

Classifications

UNSPSC

UNSPSC 11	39121004
UNSPSC 12.01	39121004
UNSPSC 13.2	39121004

Approvals

Approvals

Approvals

UL Recognized / UL Listed / cUL Recognized / cUL Listed / DNV / EAC / cULus Recognized / cULus Listed

Ex Approvals

ATEX / UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

UL Recognized 

UL Listed 

cUL Recognized 

cUL Listed 

DNV

EAC

Redundancy module, with protective coating - QUINT-DIODE/40 - 2938963

Approvals

cULus Recognized 

cULus Listed 

Drawings

Block diagram



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)