

COIL DATA

Latching (1 coil) standard(100mW) 20 °C

Order Number	Nominal Voltage VDC	Set / Reset Voltage VDC(Max.)	Coil resistance $\Omega(\pm 10\%)$	allowable Voltage VDC (Max.)
003-M-L1	3	2.25	90	8.4
005-M-L1	5	3.75	250	14
006-M-L1	6	4.5	360	17
009-M-L1	9	6.75	810	25
012-M-L1	12	9.0	1440	34
015-M-L1	15	11.25	2220	42
024-M-L1	24	18.0	4000	56

Latching (1 coil) sensitive(75mW) 20 °C

Order Number	Nominal Voltage VDC	Set / Reset Voltage VDC(Max.)	Coil resistance $\Omega(\pm 10\%)$	allowable Voltage VDC (Max.)
005-S-L1	5	4.0	330	16
006-S-L1	6	4.8	480	19
009-S-L1	9	7.2	1080	29
012-S-L1	12	9.6	1920	39
015-S-L1	15	12.0	3000	43
024-S-L1	24	19.2	7680	78

Latching (2 coil) standard(200mW) 20 °C

Order Number	Nominal Voltage VDC	Set / Reset Voltage VDC(Max.)	Coil resistance $\Omega(\pm 10\%)$	allowable Voltage VDC (Max.)
003-M-L2	3	2.25	45	6
005-M-L2	5	3.75	125	10
006-M-L2	6	4.5	180	12
009-M-L2	9	6.75	405	18
012-M-L2	12	9.0	720	24
015-M-L2	15	11.25	1125	30
024-M-L2	24	18.0	2040	48

Latching (2 coil) sensitive(150mW) 20 °C

Order Number	Nominal Voltage VDC	Set / Reset Voltage VDC(Max.)	Coil resistance $\Omega(\pm 10\%)$	allowable Voltage VDC (Max.)
005-S-L2	5	4.0	167	11.5
006-S-L2	6	4.8	240	13.8
009-S-L2	9	7.2	540	20.8
012-S-L2	12	9.6	960	27.7
015-S-L2	15	12.0	1500	34.6
024-S-L2	24	19.2	3840	55.4

Notes:When user's requirements can't be found in the above table,special order allowed.

TYPICAL CONTACT LIFE EXPECTANCY

Voltage	Power	Number of operations	
		Resistive Load	Inductive Load($\cos\phi=0.7$)
50mV	50uW	5×10^7	5×10^7
30VDC	20W	3×10^6	1×10^6
30VDC	30W	1×10^6	3×10^5
30VDC	60W	1×10^5	1.5×10^4
60VDC	20W	3×10^6	--
60VDC	30W	5×10^5	--
60VDC	60W	1×10^5	--
30VAC	40VA	3×10^6	1×10^6
30VAC	80VA	1×10^6	3×10^5
30VAC	120VA	1×10^5	1.5×10^4
60VAC	40VA	3×10^6	1×10^6
60VAC	80VA	1×10^6	3×10^5
60VAC	120VA	1×10^5	1.5×10^4
125VAC	40VA	3×10^6	1×10^6
125VAC	80VA	1×10^6	3×10^5
125VAC	125VA	1×10^5	1.5×10^4

ORDERING INFORMATION

Type	HFD2 / 012 S L2 D
Coil voltage	3, 5, 6, 9, 12, 15, 24, 48VDC(Standard Single only)
Coil Power	S: sensitive M: standard
Sort	Nil:Single side stable L1: Latching 1 coil L2: Latching 2 coils
Contact Material	Nil:AgPd60 / Ag-AuAg8 D: Ag-AuAg8 / Ag-AuAg8

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT

Telecom Relays
 HFD2

Single side stable or latching(1 coil)

Outline Dimensions

PCB layout

Wiring Diagram (Bottom view)

For latching, diagram shows the "reset" position
 Energize terminals 1 and 16 to "set"
 Reverse energize terminals 1 and 16 to "reset"

Latching(2 coils)

Outline Dimensions

PCB layout

Wiring Diagram (Bottom view)

Diagram shows the "reset" position
 Energize terminals 1 and 16 to "set"
 Energize terminals 2 and 15 to "reset"

CHARACTERISTICS CURVE

