



Part No.	型號	MKA-20101
Total Length	總長度	55 mm
Glass Length	玻璃長度	20 mm
Glass Diameter	直徑	2.54 mm
Contact Form	觸點形式	1A (SPST-NO)
Contact Position	觸點位置	SYM
Contact Material	觸點材質	Ru
Contact Rating	觸點負載	10W
Max. Switching Voltage	最大開關電壓	180VDC / 130VAC
Max. Switching Current	最大開關電流	0.5A
Contact Resistance (at initial value)	接觸電阻 (初始值)	150 mOhms
Pull In Value (AT)	啓動值	10-40
Drop Out Value (AT)	釋放值	4
Operation Time	動作時間	1.0 mSec.(Max.)
Release Time	釋放時間	0.3 mSec.(Max.)
Breakdown Voltage	耐高壓	220VDC(AT<20) 280VDC(AT>20)
Contact Capacitance	觸點電容	0.4 pF
Insulation Resistance	絕緣電阻	10 ⁹ Ohms
Resonant Frequency	諧振頻率	2.6 kHz
Operation Temperature	工作溫度範圍	-60°C ~+125°C
High Humidity	最高濕度	98% (Max.)
Operation Frequency	最高工作頻率	100 Hz
Electrical Life	電氣壽命	10 ⁷ (5V , 10mA) 10 ⁶ (24V , 250mA)
Test Coil	測試線圈	5000 550 Ohm
Leads	引線腳	Gold-Plated 鍍金
Safety	安全認證	UL

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)