



Instrumentation Grade Mini SIP Reed Relay

**RoHS
Compliant**



Schematic View



Features

- High reliability instrumentation grade reed switch with sputtered Ruthenium contacts
- 2 Form A relay ideal for high density test matrices
- Standard external magnetic shield
- Coil suppression diode
- High insulation resistance
- Hermetically sealed contacts for long life

Contact Form: 2 Form A (DPST-NO)

Coil Data

Nominal Coil Voltage	Nominal Coil Resistance	Max. Operating Voltage	Min. Release Voltage	Max. Coil Voltage
(V DC)	$\pm 10\% \Omega$	(V DC)	(V DC)	(V DC)
5	375	3.8	0.4	7

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Contact Rating


Switching Power (Max.)	: 10W
Switching Voltage (Max.)	: 200V DC
Switching Current (Max.)	: 0.5A
Carrying Current (Max.)	: 1.5A

Specifications

Contact Resistance (Initial) (Max.)	: 150m Ω
Operate Time - Including Bounce Time (Typ.)	: 0.75ms (@ Nominal Voltage)
Release Time (Typ.)	: 0.5ms
Insulation Resistance @ 100V, 20°C, 40% RH	: 10 ¹² Ω (Min.)
Dielectric Strength (Min.)	: Across Contacts 200V DC/peak AC Contacts to Coil 200V DC/peak AC Contacts / Shield to Coil 1500V DC/peak AC
Capacitance Across Open Contacts (Typ.)	: 1pF
Capacitance Open Contacts to Coil (Typ.)	: 1.4pF
Vibration	: 20G
Shock	: 50G
Operating Temperature	: -40°C to +85°C
Storage Temperature	: -40°C to +100°C
Life Expectancy @ Specified Load	: 500 × 10 ⁶ ops (1V DC, 10mA)

Instrumentation Grade Mini SIP Reed Relay

Dimensions



Dimensions : Inches (Millimetres)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Part Number Table

Description	Part Number
Reed Relay, w/ External Shield + Diode, DPST-NO, 5V DC, 375Ω, 200V DC, 0.5A, THT	MC3570-1421-054

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell Limited 2016.